

Hood type dishwasher - up to 60 racks, 1080 plates / 2160 glasses / hour



Accessories not included

Technical Data

Teeninear Data	
20mm inner /	
25mm outer diam.	
R 3/4" inside 0.5 - 10 bar 55-65°C ²⁾	
2500mm - no plug	
Available as op-	
tional kits	
60 sec.	
90 sec.	
120 sec.	
2.5 litres / rack	
21 litres	
2.5kW interlocked	
415/50 / 3NE	
6.15kW	
7kW	
0.7kW	
628mm	
440mm	
65 dB(A)	
appr.105kg	


¹⁾ To reach the set rinse temperature even with cold water connection, the actual cycles times extend accordingly


Water hardness should not exceed 3°dH, if higher we recommend using a water softener.

If mineral content is high a demineraliser may be advisable.

Product Advantages:

- **READY TO INSTALL** incl. drain pump, fill & drain hoses, 3 phase power lead & non-return valve
- RINSE PRESSURE PUMP to guarantee rinse pressure and volume
- **GeniusX**² **advanced filter system** with pre-wash function, reduces detergent consumption by up to 30%
- Fully enclosed 4 sided INSULATED hood design -avoiding loss of energy / steam & minimizing noise
- EASY-LIFT hood 50% less effort required to open hood
- SMARTRONIC single button control with colour coded status and cycle indication
- Optimum hygienic deep drawn tank with coved corners (no welds) and SELF-CLEANING CYCLE
- Hygiene program ACTIVE and hygiene tab
 INTENSIVE: removes calcium carbonate and other deposits from tank wall
- · Chemical dispensers available as optional kits
- Optional Heat recovery E-SAVE waste water heat recovery system via integral heat exchanger saves up to 6.5kW Model AMX-R
- Includes 1 plate & flat rack, plus cutlery basket
- Back flow prevention device as standard to meet Watermark Approval and ATS 5200.101
- MADE IN GERMANY





²⁾ Cold water connection for AMX-R