



ICE & REFRIGERATION

PRODUCT CATALOGUE 6 JULY 2015



Invention & Reliability in Foodservice Equipment

www.hoshizaki.com.au

CONTENTS

PRODUCT CATALOGUE 6 JULY 2015



6

BUILT ON STRONG FOUNDATIONS

7

ICE MAKERS - HOSHIZAKI ICE MACHINES

9

Ice Cube Sizes & Shapes

11

Cube Ice - IM Series

13

IM-30CNE-25

15

IM-45CNE-25

17

IM-45CNE-28

19

IM-45NE-25

21

IM-65NE-25

23

IM-100CNE-21

25

IM-130NE-21

27

IM-130NE-28

29

IM-240NE-21

31

IM-240NE-28

33

IM-240ANE-28

35

IM-240AWNE-28

37

IM-240DNE/XNE Series

39

Flake Ice - FM Series

40

FM-150KE Series

42

FM-150KE-50 Series

44

FM-300AKE Series

46

FM-480AKE Series

48

FM-750AKE Series

50

FM-1000AKE Series

52

FM-1200ALKE Series

54

FM-1800ALKE Series

56

Crescent Ice - KM Series

57

KM-30A

59

KM-50A

61

KM-75A

63

KM-100A

65

KM-125A

67

KMD-201AA

69

KMD-270AA

71

KM-650MAH

73

KM-900MAH

Continued...



CONTENTS

PRODUCT CATALOGUE 6 JULY 2015



75	KM-1301SAH
77	KM-1301SWH
79	Cubelet Ice - Dispenser Series
80	DCM-60KE-P Ice & Water Dispenser
82	DCM-120KE-P Ice & Water Dispenser
84	DB-200H Sanitary Ice Cube Dispenser
86	Ice Storage Bins & Top Kits
87	B-301SA
89	B-501SA
91	B-801SA
93	B-1300SS
95	B-1500SS
97	Water Filters
99	PROFESSIONAL SERIES REFRIGERATION & FREEZERS
101	Product Highlights
104	Professional Counter Refrigeration & Freezers
105	RTE-120SDA-GN Counter Refrigerator
107	FTE-120SDA-GN Counter Freezer
109	RTE-170SDA-GN Counter Refrigerator
111	FTE-170SDA-GN Counter Freezer
113	Professional Upright Reach in Refrigeration & Freezers
114	HRE-70B Upright Reach In Refrigerator
116	HFE-70B Upright Freezer
118	HRE-140B Upright Reach In Refrigerator
120	HFE-140B Upright Reach In Freezer
122	COMMERCIAL SERIES REFRIGERATION & FREEZERS
124	Commercial Counter Series Refrigeration & Freezers
125	RTC-120MDA Counter Refrigerator
127	RTC-120MNA Counter Refrigerator
129	FTC-120MDA Counter Freezer
131	FTC-120MNA Counter Freezer
133	RTC-150MDA Counter Refrigerator
135	RTC-150MNA Counter Refrigerator
137	FTC-150MDA Counter Freezer
139	FTC-150MNA Counter Freezer
141	RTC-180MDA Counter Refrigerator

Continued...



CONTENTS

PRODUCT CATALOGUE 6 JULY 2015



143 RTC-180MNA Counter Refrigerator

145 FTC-180MDA Counter Freezer

147 FTC-180MNA Counter Freezer

149 **Commercial Series Upright Reach In Refrigeration & Freezers**

150 HRE-77MA Upright Refrigerator

152 HFE-77MA Upright Freezer

154 HRE-127MA Upright Refrigerator

156 HFE-127MA Upright Freezer

158 HRE-147MA Upright Refrigerator

160 HFE-147MA Upright Freezer

162 HRE-187MA Upright Refrigerator

164 HFE-187MA Upright Freezer

166 **EURO LINE REFRIGERATION & FREEZERS**

168 **Hoshizaki Euro Line Counter Refrigeration & Freezers**

169 Counter Preparation Bench

171 Pizza Preparation Bench

173 Saladette Preparation Bench

175 **Hoshizaki Euro Line Upright Refrigeration & Freezers**

176 Compact 410 Glass Door Refrigerator

178 Midi 425 Glass Door Refrigerator

180 Midi 425 Glass Door Freezer

182 Midi 625 Glass Door Refrigerator

184 Midi 625 Glass Door Freezer

186 **AHT IMPULSE COOLERS**

188 AHT Fancy Slim Impulse Cooler

189 AHT 65 BC RC Impulse Cooler

190 AHT AC Slim Impulse Cooler

191 AHT AC S Impulse Cooler

192 AHT AC M Impulse Cooler

193 AHT AC XL Impulse Cooler

194 **SUSHI CABINETS**

196 HNC-120BE-L Counter Showcase

198 HNC-150BE-L Counter Showcase

200 HNC-180BE-R-B Counter Showcase

202 HNC-210BE-R-B Counter Showcase

204 **HOSHIZAKI SPARE PARTS**

Continued...



CONTENTS

PRODUCT CATALOGUE 6 JULY 2015

205

ACCREDITATION AND TERMS



BUILT ON STRONG FOUNDATIONS

OUR COOL AND CLEAN MISSION

With over 60 years of experience in the commercial kitchen equipment and food service markets, Hoshizaki is a global market leader.

Hoshizaki designed and developed Japan's first fully automatic ice maker and from this pioneering base we have an ice making and refrigeration product range that exceeds expectations in the demanding sectors of food, beverage, bars and restaurants, bio-science, healthcare and education.

Hoshizaki has rightfully gained an international reputation for sustainable innovation, durability and reliability. All machines are designed and specified by Hoshizaki's dedicated Japanese Research and Development team, which ensures Hoshizaki continues to devise innovative and sustainable products that cement the company's position as one of the world's visionary suppliers.

The company is noted for developing energy and water efficient, environmentally friendly (Hydro Fluorocarbon free) ice makers, adding value for the end-user through cost-saving and sustainability. Hoshizaki also innovates in the sectors it operates, for example in hospitality end-users can choose ice-makers that produce different types of ice from ball ice to flaked, which make the difference in quality beverages such as cocktails.

Find out more. Please visit www.hoshizaki.com.au





ICE MAKERS - HOSHIZAKI ICE MACHINES



Invention & Reliability in Foodservice Equipment

www.hoshizaki.com.au

ICE MAKERS - HOSHIZAKI ICE MACHINES

Hoshizaki is widely considered to be one of the world's leading manufacturers of ice makers. Our superior reliability ensures customers can depend on our ice machines day in, day out, year after year. Here are just a few reasons why...

ICE MACHINE RELIABILITY

Hoshizaki is the world's number one ice maker, with over 60 years of creating the world's best ice. Our product engineering, manufacture quality control and quality of internal components are what make Hoshizaki ice machines the industry standard.

We are also the only Australian company in our industry to achieve three externally recognised certifications for our Quality, Safety and Environmental systems. In addition Hoshizaki Ice Makers & Storage Bins are HACCP certified.

THE WORLD'S BEST ICE...

Hoshizaki ice machines consistently and reliably create better ice than any other ice makers;

- *the ice is clear and hard, not cloudy*
- *the ice presents very well, particularly in spirit drinks*
- *the ice has the highest displacement than any other ice*
- *the ice retains its shape; the cube ice is a genuine cube*
- *the crescent ice allows pouring and nipping of spirits without splash*
- *the ice doesn't bridge while in the ice storage bin*
- *the ice has the slowest melt rate, because it is clear and hard*

COMMERCIAL ICE MAKERS

Our commercial ice machines range encompasses many industrial ice makers that make different types of ice for different uses across a wide span of industry sectors. However, all our ice machines are of the high quality standard that is associated with Hoshizaki.

Models include ice makers for cube ice, cubelet ice, crescent ice, flake ice, scale ice and ice dispensers with models suitable for a small café or bar right through to large, modular, industrial ice machine models.

ICE MACHINE RESEARCH & DEVELOPMENT

All ice machines are originally designed and specified by a massive Japanese Research & Development team employing over 150 engineers. The basic designs and major component parts are specified for a global market meaning that Hoshizaki ice machines will effortlessly and quickly achieve outstanding levels of efficiency in ambient temperatures of between 40°C and 10°C – even in humid environments.


Hoshizaki ice machine parts are precision engineered exclusively for each ice maker to further enhance the most efficient operation. Our ice storage bins are foam injected with insulated, precision made doors with gaskets to create a closed environment that minimises meltage and thus decreases the number of ice production cycles.



ICE CUBE SIZES & SHAPES

ICE CUBE SIZES


Hoshizaki ice machines produce exceptionally hard, pure ice cubes.



* Size of Ice Cube mentioned in brackets () is reflected in product names of the IM Series, eg (21) in IM-CNE-21 refers to a Cube Size Small.

ICE CUBE SIZES & SHAPES

ICE SIZES & SHAPES



*Contact Hoshizaki Sales office for price & availability.

CUBE ICE - IM SERIES

IM PRODUCT HIGHLIGHTS



Hoshizaki IM Machines utilise a closed cell ice making system that has an automatic flush cycle.



A stainless steel exterior with integrated door handles provides a hygienic and high quality finish.



Removeable door gaskets prevent any heat and contamination from entering the bin and make the Hoshizaki product easy to clean and maintain.



A closed water circuit offers the ultimate contamination protection, by reducing the number of points at which impurities can enter the ice making process.



An easily cleanable air filter allows users to carry out a routine cleaning schedule themselves, extending the life expectancy of your Hoshizaki ice maker, and cutting the frequency and cost of maintenance call-outs.




Ice machines are computer controlled so the ice making process is optimised under varying circumstances without the need for physical adjustments.

Foam injected polyurethane for outstanding insulation (HFC free) preserves the quality and consistency of the ice produced longer than any other machine available. This reduces the number of production cycles, saving energy and money.




CUBE ICE - IM SERIES


ICE PRODUCTION PROCESS




With the water plate closed against the underside of the evaporator, the water circuit is closed to both outside contamination and water loss under normal circumstances. Crucially, each cube is made individually by a dedicated spray to ensure the highest possible ice quality.



As the ice cube slowly forms the spray continues until the end of the cycle. No fresh water is required as the internal reservoir capacity is adequate for a full cycle of ice.




When the cube is fully formed the electronic controller initiates a hot gas defrost cycle. The water plate opens and the hot gas slowly warms the evaporator.



The ice will drop from the evaporator into the ice bin. The water plate will be rinsed with fresh water to remove any remaining particles before it starts to close again. Fresh water continues to enter until the reservoir is full to enable a new freeze cycle to commence.

IM-30CNE-25



Medium

Product Specifications





COOLING	Air
WEIGHT	Net: 34kg Packed: 38kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R134a
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 22kg Air temp: 21°C Water temp: 15°C - 18kg Air temp: 32°C Water temp: 21°C - 18kg
ICE PRODUCTION PER CYCLE	0.27kg / 21pcs
FREEZE CYCLE	19mins
MAX STORAGE CAPACITY	11.5kg
BIN CONTROL	6kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000001	IM-30CNE-25	\$2916.90



IM-30CNE-25




IM-45CNE-25



WaterMark

ATS 5200.105
22349, 22350, 22351



Product Specifications





COOLING	Air
WEIGHT	Net: 48kg Packed: 55kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R134a
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 35kg Air temp: 21°C Water temp: 15°C - 32kg Air temp: 32°C Water temp: 21°C - 27kg
ICE PRODUCTION PER CYCLE	0.55kg / 42pcs
FREEZE CYCLE	22mins
MAX STORAGE CAPACITY	15kg
BIN CONTROL	8kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000090	IM-45CNE-25	\$3598.00
91000095	IM-45CNE-28	\$3391.50



IM-45CNE-25




IM-45CNE-28



WaterMark

ATS 5200.105
22349, 22350, 22351



Product Specifications





COOLING	Air
WEIGHT	Net: 48kg Packed: 55kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R134a
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 36kg Air temp: 21°C Water temp: 15°C - 32kg Air temp: 32°C Water temp: 21°C - 29kg
ICE PRODUCTION PER CYCLE	0.67kg / 30pcs
FREEZE CYCLE	28mins
MAX STORAGE CAPACITY	15kg
BIN CONTROL	8kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000090	IM-45CNE-25	\$3598.00
91000095	IM-45CNE-28	\$3391.50



IM-45CNE-28




IM-45NE-25



WaterMark

ATS 5200.105
22349, 22350, 22351



Medium

Product Specifications


COOLING	Air
WEIGHT	Net: 45kg Packed: 51kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R134a
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 35kg Air temp: 21°C Water temp: 15°C - 32kg Air temp: 32°C Water temp: 21°C - 27kg
ICE PRODUCTION PER CYCLE	0.5kg / 42pcs
FREEZE CYCLE	22mins
MAX STORAGE CAPACITY	18kg
BIN CONTROL	10kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000089	IM-45NE-25	\$3391.50



IM-45NE-25




IM-65NE-25



WaterMark

ATS 5200.105
22349, 22350, 22351



Medium

Product Specifications




COOLING	Air
WEIGHT	Net: 53kg Packed: 60kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R134a
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 45kg Air temp: 21°C Water temp: 15°C - 44kg Air temp: 32°C Water temp: 21°C - 37kg
ICE PRODUCTION PER CYCLE	0.67kg / 56 pcs
FREEZE CYCLE	22mins
MAX STORAGE CAPACITY	26kg
BIN CONTROL	18kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000097	IM-65NE-25	\$4374.30



IM-65NE-25



IM-100CNE-21







Product Specifications	
Cooling	Air
Weight	Net: 77kg Gross: 88kg
AC Supply Voltage	220 - 240V / 50Hz
Refrigerant	R134a
Ambient	1 - 40°C
Water Temp	5 - 35°C
Water Pressure	70 - 800kPa
Ice Production Per 24 Hours (Approx)	Air temp: 10°C Water temp: 10°C - 90kg Air temp: 21°C Water temp: 15°C - 85kg Air temp: 32°C Water temp: 21°C - 62kg
Ice Production Per Cycle	1.15kg / 190pcs
Freeze Cycle	17min
Max Storage Capacity	38kg
Bin Control	23kg

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
91000117	IM-100CNE-21	\$7000.00



IM-100CNE-21




IM-130NE-21



WaterMark

ATS 5200.105
22349, 22350, 22351



Small

Product Specifications


COOLING	Air
WEIGHT	Net: 76kg Packed: 84kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 104kg Air temp: 21°C Water temp: 15°C - 95kg Air temp: 32°C Water temp: 21°C - 82kg
ICE PRODUCTION PER CYCLE	1.15kg / 190 pcs
FREEZE CYCLE	19mins
MAX STORAGE CAPACITY	50kg
BIN CONTROL	28kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000007	IM-130NE-21	\$6562.50
91000106	IM-130NE-28	\$6022.80



IM-130NE-21




IM-130NE-28



WaterMark

ATS 5200.105
22349, 22350, 22351



Large

Product Specifications


COOLING	Air
WEIGHT	Net: 76kg Packed: 84kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 104kg Air temp: 21°C Water temp: 15°C - 100kg Air temp: 32°C Water temp: 21°C - 88kg
ICE PRODUCTION PER CYCLE	1.8kg / 80pcs
FREEZE CYCLE	22mins
MAX STORAGE CAPACITY	50kg
BIN CONTROL	28kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000106	IM-130NE-28	\$6022.80
91000007	IM-130NE-21	



IM-130NE-28



IM-240NE-21






Product Specifications	
COOLING	Air
WEIGHT	Net: 111kg Packed: 122kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 180kg Air temp: 21°C Water temp: 15°C - 175kg Air temp: 32°C Water temp: 21°C - 165kg
ICE PRODUCTION PER CYCLE	2.38kg / 140pcs
FREEZE CYCLE	11mins
MAX STORAGE CAPACITY	110kg
BIN CONTROL	80kg


Product Range		
PART NO.	DESCRIPTION	LIST PRICE
91000112	IM-240NE-21	\$9093.00
91000091	IM-240NE-28	\$8748.60



IM-240NE-21



IM-240NE-28






Product Specifications	
COOLING	Air
WEIGHT	Net: 111kg Packed: 122kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 230kg Air temp: 21°C Water temp: 15°C - 210kg Air temp: 32°C Water temp: 21°C - 195kg
ICE PRODUCTION PER CYCLE	3.2kg / 140pcs
FREEZE CYCLE	20mins
MAX STORAGE CAPACITY	110kg
BIN CONTROL	80kg

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
91000112	IM-240NE-21	\$9093.00
91000091	IM-240NE-28	\$8748.60



IM-240NE-28




IM-240ANE-28



WaterMark

ATS 5200.105
22349, 22350, 22351



Large

Product Specifications




COOLING	Air
WEIGHT	Net: 80kg Packed: 91kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 220kg Air temp: 21°C Water temp: 15°C - 205kg Air temp: 32°C Water temp: 21°C - 160kg
ICE PRODUCTION PER CYCLE	3.2kg / 140pcs
FREEZE CYCLE	20mins
MAX STORAGE CAPACITY	Select Bin

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000098	IM-240ANE	\$7164.15
91000113	IM-240AWNE	\$7616.70



IM-240ANE-28




IM-240AWNE-28



WaterMark

ATS 5200.105
22349, 22350, 22351



Large

Product Specifications


COOLING	Water
WEIGHT	Net: 80kg Packed: 91kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODCUTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 230kg Air temp: 21°C Water temp: 15°C - 215kg Air temp: 32°C Water temp: 21°C - 205kg
ICE PRODUCTION PER CYCLE	3.2kg / 140pcs
FREEZE CYCLE	20mins
MAX STORAGE CAPACITY	Select Bin

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000098	IM-240ANE	\$7164.15
91000113	IM-240AWNE	\$7616.70



IM-240AWNE-28




IM-240DNE/XNE SERIES



WaterMark

ATS 5200.105
22349, 22350, 22351



Product Specifications

COOLING	Air
WEIGHT - DNE SERIES	Net: 88kg Packed: 106kg
WEIGHT - XNE SERIES	Net: 84kg Packed: 102kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 190kg Air temp: 21°C Water temp: 15°C - 180kg Air temp: 32°C Water temp: 21°C - 165kg
ICE PRODUCTION PER CYCLE	2.1kg / 360pcs
FREEZE CYCLE	15min


Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000009	IM-240DNE-21	\$7607.25
91000109	IM-240DNE-28	\$8280.30
91000099	IM-240DNE-32	\$7353.15
91000079	IM-240XNE-21	\$6804.00




IM-240DNE/XNE SERIES

IM-240DNE-21



IM-240XNE-21



FLAKE ICE - FM SERIES

FM PRODUCT HIGHLIGHTS

The FM series produce flake/nugget ice, with the nugget ice compressed during production to make it long-lasting. The flake and nugget ice is popular for a variety of cooling purposes including the display of fish and fresh produce, and also in the medical world for cooling blood and organs.



The characteristics of the ice produced by Hoshizaki ice makers means that 'freeze-burn' is no longer an issue when displaying fresh fish or produce.

Carbon Auger bearings are used within this range and they are far more robust than roller bearings, enhancing product life expectancy and also reducing maintenance costs.



Flake



Nugget



Cubelet Ice

FM-150KE SERIES



WaterMark

ATS 5200.105
22349, 22350, 22351







Product Specifications

COOLING	Air
WEIGHT	Net: 71kg Packed: 82kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R134a
AMBIENT	5°C - 40°C
WATER TEMP	5°C - 30°C
WATER PRESSURE	50 - 800kPa
FM-150KE ICE PRODUCTION PER 24 HOURS (APPROX)	Air Temp: 10°C Water temp: 10°C - 150kg Air Temp: 21°C Water temp: 15°C - 130kg Air Temp: 32°C Water temp: 21°C - 110kg
FM-150KE-N ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 140kg Air temp: 21°C Water temp: 15°C - 120kg Air temp: 32°C Water temp: 21°C - 100kg
MAX STORAGE CAPACITY	FM-150KE: 26kg FM-150KE-N: 32kg
BIN CONTROL	FM-150KE: 21kg FM-150KE-N: 27kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000101	FM-150KE	\$6846.00

FM-150KE SERIES



FM-150KE-50 SERIES



WaterMark

ATS 5200.105
22349, 22350, 22351





Product Specifications

COOLING	Air
WEIGHT	Net: 81kg Packed: 94kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R134a
AMBIENT	5°C - 40°C
WATER TEMP	5°C - 30°C
WATER PRESSURE	50 - 800kPa
FM-150KE-50 ICE PRODUCTION PER 24 HOURS (APPROX)	Air Temp: 10°C Water temp: 10°C - 150kg Air Temp: 21°C Water temp: 15°C - 130kg Air Temp: 32°C Water temp: 21°C - 110kg
FM-150KE-50-N ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 140kg Air temp: 21°C Water temp: 15°C - 120kg Air temp: 32°C Water temp: 21°C - 100kg
STORAGE BIN	FM-150KE-50: 57kg FM-150KE-50-N: 65kg
BIN CONTROL	FM-150KE-50: 41kg FM-150KE-50-N: 47kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000102	FM-150KE-50	\$7607.25
91000086	FM-150KE-50-N	\$7608.30

FM-150KE-50 SERIES



FM-300AKE SERIES



WaterMark

ATS 5200.105
22349, 22350, 22351



FM-300AKE+B-301SA



Product Specifications


COOLING	Air
WEIGHT	Net: 80kg Packed: 87kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 15Amps
REFRIGERANT	R404A
AMBIENT	5 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
FM-300AKE ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 320kg Air temp: 21°C Water temp: 15°C - 260kg Air temp: 32°C Water temp: 21°C - 200kg
FM-300AKE-N ICE PRODUCTION PER 24 HOURS	Air temp: 10°C Water temp: 10°C - 270kg Air temp: 21°C Water temp: 15°C - 225kg Air temp: 32°C Water temp: 21°C - 180kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000103	FM-300AKE	\$9002.70



FM-300AKE SERIES



FM-480AKE SERIES



WaterMark

ATS 5200.105
22349, 22350, 22351



FM-480AKE+B-3015A



Product Specifications


COOLING	Air
WEIGHT	Net: 95kg Packed: 102kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 15Amps
REFRIGERANT	R404A
AMBIENT	5 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
FM-480AKE ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 500kg Air temp: 21°C Water temp: 15°C - 452kg Air temp: 32°C Water temp: 21°C - 325kg
FM-480AKE-N ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 430kg Air temp: 21°C Water temp: 15°C - 360kg Air temp: 32°C Water temp: 21°C - 290kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000104	FM-480AKE	\$10461.15



FM-480AKE SERIES



FM-750AKE SERIES



WaterMark

ATS 5200.105
22349, 22350, 22351



FM-750AKE+B-S015A



Product Specifications


COOLING	Air
WEIGHT	Net: 133kg Packed: 143kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 15Amps
REFRIGERANT	R404A
AMBIENT	5 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
FM-750AKE ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 750kg Air temp: 21°C Water temp: 15°C - 650kg Air temp: 32°C Water temp: 21°C - 100kg
FM-750AKE-N ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 140kg Air temp: 21°C Water temp: 15°C - 120kg Air temp: 32°C Water temp: 21°C - 390kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000080	FM-750AKE	\$18067.35



FM-750AKE SERIES



FM-1000AKE SERIES



WaterMark

ATS 5200.105
22349, 22350, 22351



FM-1000AKE + B-501SA



Product Specifications


COOLING	Air
WEIGHT	Net: 146kg Packed: 156kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 15Amps
REFRIGERANT	R404A
AMBIENT	5 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
FM-1000AKE ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 1030kg Air temp: 21°C Water temp: 15°C - 890kg Air temp: 32°C Water temp: 21°C - 740kg
FM-1000AKE-N ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 860kg Air temp: 21°C Water temp: 15°C - 730kg Air temp: 32°C Water temp: 21°C - 590kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000081	FM-1000AKE (N)	\$19023.90



FM-1000AKE SERIES



FM-1200ALKE SERIES



WaterMark

ATS 5200.105
22349, 22350, 22351



FM-1200ALKE+B-5015A



Product Specifications





COOLING	Air
WEIGHT	Net: 98kg Packed: 108kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 15Amps
REFRIGERANT	R404A
AMBIENT	5 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
FM-1200ALKE ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 1200kg Air temp: 21°C Water temp: 15°C - 1040kg Air temp: 32°C Water temp: 21°C - 890kg
FM-1200ALKE-N ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 1060kg Air temp: 21°C Water temp: 15°C - 920kg Air temp: 32°C Water temp: 21°C - 800kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000082	FM-1200ALKE (N)	\$18067.35



FM-1200ALKE SERIES



FM-1800ALKE SERIES



WaterMark

ATS 5200.105
22349, 22350, 22351



FM-1800ALKE-B-8015A



Product Specifications



COOLING	Air
WEIGHT	Net: 140kg Packed: 155kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 15Amps
REFRIGERANT	R404A
AMBIENT	5 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
FM-1800ALKE ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 1800kg Air temp: 21°C Water temp: 15°C - 1560kg Air temp: 32°C Water temp: 21°C - 1335kg
FM-1800ALKE-N ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 1590kg Air temp: 21°C Water temp: 15°C - 1380kg Air temp: 32°C Water temp: 21°C - 1200kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000083	FM-18000ALKE (N)	\$24091.20



FM-1800ALKE SERIES



CRESCENT ICE - KM SERIES

KM PRODUCT HIGHLIGHTS



KM machines produce clear, crescent shaped ice. The unique shape is extremely versatile and extends from the splash-free serving of post mix soft drinks through to diverse applications such as fish transportation, display and even laser therapy.



This range includes a double-sided stainless steel evaporator, which requires fewer cycles to produce a full bin of ice, thereby reducing energy consumption.



All units are easily accessible for service via the front of unit. This reduces the time it takes to complete maintenance costs.



Ice machines are computer controlled so the ice making process is optimised under varying circumstances without the need for physical adjustments.



An easily cleanable air filter allows users to carry out a routine cleaning schedule themselves, extending the life expectancy of the ice maker, and cutting the frequency and cost of maintenance call-outs.

KM-30A



WaterMark

ATS 5200.105
22349, 22350, 22351



CRESCENT ICE



Product Specifications




COOLING	Air
WEIGHT	Net: 39kg Packed: 49kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R134a
AMBIENT	1°C - 40°C
WATER TEMP	5°C - 30°C
WATER PRESSURE	70 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 36kg Air temp: 21°C Water temp: 15°C - 32kg Air temp: 32°C Water temp: 21°C - 25kg
ICE PRODUCTION PER CYCLE	0.71kg / 80pcs
FREEZE CYCLE	30mins
MAX STORAGE CAPACITY	16kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000030	KM-30A	\$2430.75
91000031	KM-50A	\$2964.15
91000032	KM-75A	\$3984.75



KM-30A



KM-50A



WaterMark

ATS 5200.105
22349, 22350, 22351



CRESCENT ICE



Product Specifications


COOLING	Air
WEIGHT	Net: 46kg Packed: 58kg
AC SUPPLY VOLTAGE	220 - 240V /50Hz 10Amps
REFRIGERANT	R134a
AMBIENT	1°C - 40°C
WATER TEMP	5°C - 35°C
WATER PRESSURE	70 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 52kg Air temp: 21°C Water temp: 15°C - 50kg Air temp: 32°C Water temp: 21°C - 41kg
ICE PRODUCTION PER CYCLE	0.95kg / 110pcs
FREEZE CYCLE	25mins
MAX STORAGE CAPACITY	23kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000030	KM-30A	\$2430.75
91000031	KM-50A	\$2964.15
91000032	KM-75A	\$3984.75



KM-50A



KM-75A



WaterMark

ATS 5200.105
22349, 22350, 22351



CRESCENT ICE



Product Specifications


COOLING	Air
WEIGHT	Net: 51kg Packed: 64kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R134a
AMBIENT	1°C - 40°C
WATER TEMP	5°C - 35°C
WATER PRESSURE	70 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 72kg Air temp: 21°C Water temp: 15°C - 70kg Air temp: 32°C Water temp: 21°C - 55kg
ICE PRODUCTION PER CYCLE	1.25kg / 130pcs
FREEZE CYCLE	24mins
MAX STORAGE CAPACITY	40kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000030	KM-30A	\$2430.75
91000031	KM-50A	\$2964.15
91000032	KM-75A	\$3984.75



KM-75A



KM-100A



WaterMark

ATS 5200.105
22349, 22350, 22351



CRESCENT ICE



Product Specifications


COOLING	Air
WEIGHT	Net: 62kg Packed: 75kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1°C - 40°C
WATER TEMP	5°C - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water Temp: 10°C - 101kg Air temp: 21°C Water Temp: 15°C - 88kg Air temp: 32°C Water Temp: 21°C - 64kg
ICE PRODUCTION PER CYCLE	1.7kg / 182pcs
FREEZE CYCLE	26mins
MAXIMUM STORAGE CAPACITY	45kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000055	KM-100A	\$5157.60
91000056	KM-125A	\$5934.60



KM-100A



KM-125A



WaterMark

ATS 5200.105
22349, 22350, 22351



CRESCENT ICE



Product Specifications


COOLING	Air
WEIGHT	Net: 70kg Packed: 85kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1°C - 40°C
WATER TEMP	5°C - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water Temp: 10°C - 128kg Air temp: 21°C Water Temp: 15°C - 115kg Air temp: 32°C Water Temp: 21°C - 102kg
ICE PRODUCTION PER CYCLE	2.1kg / 238pcs
FREEZE CYCLE	24mins
MAXIMUM STORAGE CAPACITY	55kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000055	KM-100A	\$5157.60
91000056	KM-125A	\$5934.60



KM-125A



KMD-201AA




WaterMark

ATS 5200.105
22349, 22350, 22351



CRESCENT ICE



Allows installation on 560mm
(22") wide drink dispenser

Product Specifications


COOLING	Air
WEIGHT	Net: 57kg Packed: 73kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	70 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 205kg Air temp: 21°C Water temp: 15°C - 182kg Air temp: 32°C Water temp: 21°C - 157kg
ICE PRODUCTION PER CYCLE	3.8kg / 416pcs
FREEZE CYCLE	27mins
MAX STORAGE CAPACITY	Select Bin

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000067	KMD-201AA	\$5505.15



KMD-201AA



KMD-270AA




WaterMark

ATS 5200.105
22349, 22350, 22351



CRESCENT ICE



Product Specifications


COOLING	Air
WEIGHT	Net: 57kg Packed: 73kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	70 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 265kg Air temp: 21°C Water temp: 15°C - 248kg Air temp: 32°C Water temp: 21°C - 221kg
ICE PRODUCTION PER CYCLE	5.7kg / 624pcs
FREEZE CYCLE	27mins
MAX STORAGE CAPACITY	Select Bin

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000111	KMD-270AA	\$6300.00



KMD-270AA



KM-650MAH




WaterMark

ATS 5200.105
22349, 22350, 22351



KM-650MAH + B-301SA



Product Specifications


COOLING	Air
WEIGHT	Net: 77kg Packed: 91kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 10Amps
REFRIGERANT	R404A
AMBIENT	7°C - 38°C
WATER TEMP	7°C - 32°C
WATER PRESSURE	68kpaG - 780kpaG
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 333kg Air temp: 21°C Water temp: 15°C - 274kg Air temp: 32°C Water temp: 21°C - 243kg
ICE PRODUCTION PER CYCLE	6.4kg / 720pcs
MAXIMUM STORAGE CAPACITY	Select storage bin

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000016	KM-650MAH	\$7644.00
91000120	KM-901MAH-E	\$10708.95
91000018	KM-1301SAH	\$13532.40
91000051	KM-1301SWH	\$12120.15



KM-650MAH



KM-900MAH




WaterMark

ATS 5200.105
22349, 22350, 22351



KM-900MAH + B-501SA



Product Specifications

COOLING	Air
WEIGHT	Net: 98kg Packed: 128kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 15Amps
REFRIGERANT	R404A
AMBIENT	7°C - 38°C
WATER TEMP	7°C - 32°C
WATER PRESSURE	68kpaG - 780kpaG
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water temp: 10°C - 429kg Air temp: 20°C Water temp: 15°C - 392kg Air temp: 30°C Water temp: 25°C - 321kg
ICE PRODUCTION PER CYCLE	6.5kg/720pcs
MAX STORAGE CAPACTIY	Select storage bin

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000016	KM-650MAH	\$7644.00
91000120	KM-901MAH-E	\$10708.95
91000018	KM-1301SAH	
91000051	KM-1301SWH	




KM-900MAH



FRONT VIEW



SIDE VIEW



BACK VIEW



KM-1301SAH




WaterMark

ATS 5200.105
22349, 22350, 22351



KM-1301SAH + B-801SA



Product Specifications




COOLING	Air
WEIGHT	Net: 120kg Packed: 143kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 15Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water Temp: 10°C - 584kg Air temp: 21°C Water Temp: 15°C - 522kg Air temp: 32°C Water Temp: 21°C - 465kg
ICE PRODUCTION PER CYCLE	13.2kg / 1440pcs
FREEZE CYCLE	35mins
MAX STORAGE CAPACITY	Select Bin

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000018	KM-1301SAH	\$13532.40
91000051	KM-1301SWH	\$12120.15



KM-1301SAH



KM-1301SWH




WaterMark

ATS 5200.105
22349, 22350, 22351



KM-1301SAH + B-801SA



Product Specifications





COOLING	Water
WEIGHT	Net: 120kg Packed: 143kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz 15Amps
REFRIGERANT	R404A
AMBIENT	1 - 40°C
WATER TEMP	5 - 35°C
WATER PRESSURE	50 - 800kPa
ICE PRODUCTION PER 24 HOURS (APPROX)	Air temp: 10°C Water Temp: 10°C - 621kg Air temp: 21°C Water Temp: 15°C - 601kg Air temp: 32°C Water Temp: 21°C - 549kg
ICE PRODUCTION PER CYCLE	13.2kg / 1440pcs
FREEZE CYCLE	32mins
MAX STORAGE CAPACITY	Select Bin

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000018	KM-1301SAH	\$13532.40
91000051	KM-1301SWH	\$12120.15



KM-1301SWH



CUBELET ICE - DISPENSER SERIES

PRODUCT HIGHLIGHTS



The New DCM-60KE



DIM-30DE

- Ice and/or water mix at the touch of a button, making it as easy and simple to use as possible and therefore ideal for self-service environments.
- Portion control can be easily set, making it easy to regulate the consumption of ice among end-users, reducing energy consumption and waste.
- Due to the auger system the water consumption is equal to the ice production.
- Ice is dispensed directly into the cup or bucket reducing the risk of contamination.

DCM-60KE-P ICE & WATER DISPENSER



WaterMark

ATS 5200.105
22349, 22350, 22351



Product Specifications


Cooling	Air
Weight	Net: 47kg Packed: 56kg
AC Supply Voltage	220 - 240V / 50Hz 10Amps
Refrigerant	R134a
Ambient	5 - 40°C
Water temp	5 - 35°C
Water pressure	50 - 780kPa
Ice production per 24 hours (approx)	Air temp: 10°C Water temp: 10°C - 60kg Air temp: 21°C Water temp: 15°C - 50kg Air temp: 32°C Water temp: 21°C - 38kg
Max Storage Capacity	1.9kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000116	DCM-60KE-P	\$7108.50
91000115	DCM-120KE-P	\$7709.10



DCM-60KE-P ICE & WATER DISPENSER



DCM-120KE-P ICE & WATER DISPENSER



WaterMark

ATS 5200.105
22349, 22350, 22351



Product Specifications


Cooling	Air
Weight	Net: 57kg Packed: 66kg
AC Supply Voltage	220 - 240V / 50Hz 10Amps
Refrigerant	R134a
Ambient	5 - 40°C
Water temp	5 - 35°C
water pressure	50 - 780kPa
Ice production per 24 hours (approx)	Air temp: 10°C Water temp: 10°C - 125kg Air temp: 21°C Water temp: 15°C - 105kg Air temp: 32°C Water temp: 21°C - 85kg
Max Storage Capacity	4kg

Product Range

PART NO.	DESCRIPTION	LIST PRICE
91000115	DCM-120KE-P	\$7709.10
91000116	DCM-60KE-P	\$7108.50



DCM-120KE-P ICE & WATER DISPENSER



DB-200H SANITARY ICE CUBE DISPENSER



WaterMark

ATS 5200.105
22349, 22350, 22351



Product Specifications


<i>Dimensions</i>	Width: 762mm Depth: 757mm Height: 1346mm
<i>Weight</i>	Net: 85kg
<i>GPO capacity</i>	10Amps
<i>Maximum Storage Capacity</i>	91kg

Product Range

<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
91000063	DB200 Dispenser	\$7528.50
91000131	Ice Dispenser DB200H with H20	\$8600.00



DB-200H SANITARY ICE CUBE DISPENSER



ICE STORAGE BINS & TOP KITS

In order to ensure ample quantities of ice at all times, Hoshizaki offers a wide range of Storage Bins that configure perfectly with Hoshizaki Ice Machines.

The stainless steel exterior provides for easy cleaning and a long lasting attractive appearance.

Sturdy construction for side by side or stacked installations and non-corrosive bin liner provide safe, sanitary storage of cube or flake ice. Foamed in place insulation in all bin walls provides dependable, low melt rate ice storage.

The size of the bins depends on several factors - the capacity of the machine, the average daily demand and the peak demand.



Storage bins, manufactured by Hoshizaki are made of stainless steel and come with legs adjustable between 90 - 120mm.



Bins are easy to clean with round edges for optimal hygiene.

B-301SA




B-301SA

<i>Product Specifications</i>	
<i>BIN CAPACITY</i>	144kg
<i>DIMENSIONS W x D x H (INCL LEGS)</i>	578mm x 820mm x 1106mm
<i>WEIGHT (NET)</i>	34kg
<i>TOP KITS: IM240D</i>	N/A
<i>TOP KITS: KM900</i>	N/A
<i>TOP KITS: IM240A, KM650, FM300, FM600</i>	No top kit required
<i>TOP KITS: KMD201, KMD270</i>	No top kit required
<i>TOP KITS: 2 x IM240A, 2 x KM650, 2 x FM300, 2 x FM600</i>	N/A
<i>TOP KITS: 2 x KMD201, 2 x KMD270</i>	N/A
<i>TOP KITS: KM1301, KM2100</i>	N/A
<i>TOP KITS: FM1000, FM1200</i>	N/A
<i>TOP KITS: FM1800</i>	N/A

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
91000025	B-301SA	\$1528.80
91000026	B-501SA	\$1924.65
91000027	B-801SA	\$2546.25
91000053	B-1300SS	\$6791.40
91000054	B-1500SS	\$7724.85

B-301SA



B-501SA




B-501SA

<i>Product Specifications</i>	
<i>BIN CAPACITY</i>	217kg
<i>DIMENSIONS W X D X H (INCL LEGS)</i>	781mm x 820mm x 1106mm
<i>WEIGHT (NET)</i>	47kg
<i>TOP KITS: IM240D</i>	N/A
<i>TOP KITS: KM900</i>	No top kit required
<i>TOP KITS: IM240A, KM650, FM300, FM600</i>	8D
<i>TOP KITS: KMD201, KMD270</i>	8D
<i>TOP KITS: 2 x IM240A, 2 x KM650, 2 x FM300, 2 x FM600</i>	N/A
<i>TOP KITS: 2 x KMD201, 2 x KMD270</i>	N/A
<i>TOP KITS: KM1301, KM2100</i>	N/A
<i>TOP KITS: FM1000, FM1200</i>	No top kit required
<i>TOP KITS: FM1800</i>	N/A

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
91000025	B-301SA	\$1528.80
91000026	B-501SA	\$1924.65
91000027	B-801SA	\$2546.25
91000053	B-1300SS	\$6791.40
91000054	B-1500SS	\$7724.85

B-501SA



B-801SA



Product Specifications





<i>BIN CAPACITY</i>	348kg
<i>DIMENSIONS W x D x H (INCL LEGS)</i>	1238mm x 820mm x 1106mm
<i>WEIGHT (NET)</i>	64kg
<i>TOP KITS: IM240D</i>	IMD
<i>TOP KITS: KM900</i>	8D + 18D
<i>TOP KITS: IM240A, KM650, FM300, FM600</i>	8D + 18D
<i>TOP KITS: KMD201, KMD270</i>	8D + 18D
<i>TOP KITS: 2 x IM240A, 2 x KM650, 2 x FM300, 2 x FM600</i>	4DM
<i>TOP KITS: 2 x KMD201, 2 x KMD270</i>	4DM + 4DR Universal
<i>TOP KITS: KM1301, KM2100</i>	No top kit required
<i>TOP KITS: FM1000, FM120</i>	18D
<i>TOP KITS: FM1800</i>	TK-1800

Product Range

<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
91000025	B-301SA	\$1528.80
91000026	B-501SA	\$1924.65
91000027	B-801SA	\$2546.25
91000053	B-1300SS	\$6791.40
91000054	B-1500SS	\$7724.85



B-801SA



B-1300SS




B-1300SS



<i>Product Specifications</i>	
<i>BIN CAPACITY</i>	578kg
<i>DIMENSIONS W x D x H (INCL LEGS)</i>	1218mm x 1040mm x 1680mm
<i>WEIGHT</i>	140kg
<i>TOP KITS: IM240D</i>	Universal
<i>TOP KITS: KM900</i>	Universal
<i>TOP KITS: IM240A, KM650, FM300, FM600</i>	Universal
<i>TOP KITS: KMD201, KMD270</i>	Universal
<i>TOP KITS: 2 x IM240A, 2 x KM650, 2 x FM300, 2 x FM650</i>	Universal
<i>TOP KITS: 2 x KMD201, 2 x KMD270</i>	Universal
<i>TOP KITS: FM1000, FM1200</i>	Universal
<i>TOP KITS: FM1800</i>	Universal

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
91000025	B-301SA	\$1528.80
91000026	B-501SA	\$1924.65
91000027	B-801SA	\$2546.25
91000053	B-1300SS	\$6791.40
91000054	B-1500SS	\$7724.85

B-1300SS



TOP VIEW
B-1150/1300SS



B-1500SS




B-1500SS

<i>Product Specifications</i>	
<i>BIN CAPACITY</i>	680kg
<i>DIMENSIONS W x D x H (INCL LEGS)</i>	1523mm x 1040mm x 1578mm
<i>WEIGHT (NET)</i>	159kg
<i>TOP KITS: IM240D</i>	Universal
<i>TOP KITS: KM900</i>	Universal
<i>TOP KITS: IM240A, KM650, FM300, FM600</i>	Universal
<i>TOP KITS: KMD201, KMD270</i>	Universal
<i>TOP KITS: 2 x IM240A, 2 x KM650, 2 x FM300, 2 x FM600</i>	Universal
<i>TOP KITS: 2 x KMD201, 2 x KMD270</i>	Universal
<i>TOP KITS: KM1301, KM2100</i>	Universal
<i>TOP KITS: FM1000, FM1200</i>	Universal
<i>TOP KITS: FM1800</i>	Universal

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
91000025	B-301SA	\$1528.80
91000026	B-501SA	\$1924.65
91000027	B-801SA	\$2546.25
91000053	B-1300SS	\$6791.40
91000054	B-1500SS	\$7724.85



B-1500SS



WATER FILTERS



Product Specifications	
87000104 - WATER FILTER HLF10 COMPLETE WITH BRACKET SMALL	Suitable for: IM's 30, 45, 65, 100 NE & CNE Units KM's 30, 50, 75, 100, 125 Units FM & (N) 120, 150 Units Dispensers DCM60, DCM110, DIM30 Units
87000105 - WATER FILTER HLF20 COMPLETE WITH BRACKET LARGE	Suitable for: IM's 130 & all 240 Units KM's 201, 650 and KMD-270 Units FM & (N) 300, 600 Units Dispensers DCM230 Units
87000123 - FILTER PARALLEL HLF32 COMPLETE WITH BRACKET EXTRA LARGE	Suitable for: KM's 900, 1300 - 2100 Units FM 1200 & 1800 Units
87000106 - REPLACEMENT HLFC10 CARTRIDGE ONLY SMALL	Suitable for: IM's 30, 45, 65, 100, NE & CNE Units KM's 30, 50, 75, 100, 125 Units FM & (N) 120, 150 Units Dispensers DCM60, DCM110, DIM30 Units
81000107 - REPLACEMENT HLFC20 CARTRIDGE ONLY LARGE	Suitable for: IM's 130 & all 240 Units KM's 201, 650 and KMD-270 Units FM & (N) 300, 600 Units Dispensers DCM230 Units
81000116 - 2M WATER SUPPLY HOSE	Connecting hose suitable for all machines
06000036 - INSTALLATION KIT (KM HEADS ONLY)	Installation kit used only for KM Units KM's 201, 650, 900, 1300 - 2100 Units KMD-270 Units



WATER FILTERS



78000098 - DRAIN PUMP

4.5m head
Low Profile

78000099 - DRAIN PUMP

Suits all self contained
ice makers

Product Range

REF NO.	PART NO.	DESCRIPTION	LIST PRICE
1	87000104	WATER FILTER HLF10 COMPLETE WITH BRACKET SMALL	\$165.43
2	87000105	WATER FILTER HLF20 COMPLETE WITH BRACKET LARGE	\$222.57
3	87000123	FILTER PARALLEL HLF32 COMPLETE WITH BRACKET EXTRA LARGE	\$499.98
4	87000106	REPLACEMENT HLFC10 CARTRIDGE ONLY SMALL	\$134.30
5	87000107	REPLACEMENT HLFC20 CARTRIDGE ONLY LARGE	\$191.43
6	81000116	2M WATER SUPPLY HOSE	\$45.71
7	06000036	INSTALLATION KIT (KM HEADS ONLY)	\$164.29
8	78000098	DRAIN PUMP	\$455.08
9	78000099	DRAIN PUMP	\$487.26



PROFESSIONAL SERIES REFRIGERATION & FREEZERS



Invention & Reliability in Foodservice Equipment

www.hoshizaki.com.au

PROFESSIONAL SERIES REFRIGERATION & FREEZERS

Hoshizaki refrigeration products are designed for kitchen professionals who demand a reliable cost effective and easy to maintain product.

Constructed from first class materials, the exterior and interior of the refrigerators and freezers are made of stainless steel. The under counters have an inside door cover of grey ABS. The temperature range for the upright refrigerators is 0°C to +16°C and -6°C to +12°C for the under counter refrigerator. The temperature range for the upright and under counter freezers are -27°C to -7°C. Both the upright and under counter series are rated to 43°C operating ambient, and HACCP approved.

Hoshizaki refrigeration is incredibly energy efficient through the use of DC fan motors. Front located removable, cleanable air filters means ease of maintenance and reduced service issues.

The upright reach in range comprises single and double door refrigerators and freezers with 631 and 1372 litre capacities respectively, while the under counter range offers two and three door models with capacities from 265 to 412 litres. Drawers are an option.

Hoshizaki refrigeration features integrated electronic controls, heavy duty castors and automatic defrost. The upright range also features self-closing, lockable doors for convenience and security.



PRODUCT HIGHLIGHTS



PRODUCT HIGHLIGHTS

STANDARD PRODUCT RANGE

This range is made up of gastronorm 2/1 cabinets and 1/1 counters, available as a refrigerator or freezer with cabinets available in single, double and split doors and counters in double and triple door.

- *Carefully designed to ensure the optimal circulation of air at all times.*
- *Refrigerated air is circulated around the cabinet to maintain the storage of foodstuffs at the correct temperature using an energy efficient DC Fan.*
- *Exterior and interior are made of stainless steel. Counters have an inside door cover of grey ABS.*
- *Temperature ranges:
Cabinet: 0 to 16 & -25 to -7
Counter: -6 to 12 & -25 to -7*
- *These counters and cabinets offer great versatility as they can be used for different types of storage as requirements change or seasonal changes dictate menu variations.*



PRODUCT HIGHLIGHTS

CUSTOMER BENEFITS

COUNTER



- The Stainless steel composition of the machine allows the worktop to double-up as a food preparation area, reducing the footprint of the machine in frequently space-restricted commercial environments.
- The compressor assembly can be easily accessed or removed from the machine, allowing easy maintenance and reducing costs*.
- An energy efficient DC fan (80% more energy efficient than AC fan) considerably reduces the amount of energy consumed by the machine, reducing its impact on both the environment and your finances.

UPRIGHT



- An energy efficient DC fan (80% more energy efficient than AC fan) considerably reduces the amount of energy consumed.
- Routine cleaning and maintenance schedules are quick and easy to carry out, facilitated by the ergonomic design of the unit.
- Machines in this range include automatically closing doors (when an angle of less than 90 degrees). This reduces the risk of doors accidentally being left open, increasing the amount of energy consumed, and avoiding product spoil.
- The front frame of the freezer cabinet is heated, which when combined with the units efficient insulation, mean that condensation cannot build up on the exterior panels of the cabinet.
- The evaporator defrost cycle of the freezer is scheduled to run every six hours, maintaining energy efficiency by reducing the build up of ice on the evaporator.

These units are supplied with castors as standard allowing them to be easily moved when looking to relocate equipment, or for cleaning purposes. Legs are optional.



PROFESSIONAL COUNTER REFRIGERATION & FREEZERS

Hoshizaki refrigeration and freezer products are designed for professional kitchens who demand a reliable easy to maintain product with a low cost of ownership.



Easy Cleaning

Removable door gaskets for easy cleaning without the need for tools



Adjustable Shelves

The counter offers one height adjustable shelf per section as standard



Hygienic Design

Dished stainless interior and base with rounded edges for easy cleaning



User friendly controller

Control panel with digital thermometer / thermostat for accurate control and easy reading. A transparent plastic cover protects against accidental adjustment of temperature and fluid spillage.



Easy Service

A compact slide out refrigeration unit for easy maintenance and service access.



Easy Maintenance

Easy access to front loaded air filter for cleaning.

RTE-120SDA-GN COUNTER REFRIGERATOR




Product Specifications	
WEIGHT	Net: 83kg Gross: 93kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz / 1
AMPERAGE	1.4A
STARTING AMPERAGE	6.8A
DEFROST SYSTEM	Heater
TEMPERATURE CONTROL	Microprocessor controlled - Adjustable from -6°C to 12°C
EFFECTIVE CAPACITY	265L
AMBIENT TEMPERATURE	5 - 43°C
REFRIGERANT	R134a
EXTERIOR	Stainless Steel, Galvanised Steel (Rear/Bottom)
INTERIOR	Stainless Steel ABS Plastic
DOOR / SHELF	2 Door / 2 Shelf
Castors	Comes standard with 76mm castors and 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000007	RTE-120SDA-GN	\$4122.30



RTE-120SDA-GN COUNTER REFRIGERATOR



FTE-120SDA-GN COUNTER FREEZER




Product Specifications	
WEIGHT	Net: 87kg Gross: 97kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz / 1
AMPERAGE	2.8A
STARTING AMPERAGE	13.0A
DEFROST SYSTEM	Glass Tube Heater
TEMPERATURE CONTROL	Microprocessor controlled - adjustable from -25°C to -7°C
EFFECTIVE CAPACITY	265L
AMBIENT TEMPERATURE	5 - 43°C
REFRIGERANT	R404A
EXTERIOR	Stainless Steel, Galvanised Steel (Rear / Bottom)
INTERIOR	Stainless Steel ABS Plastic
DOOR / SHELF	2 Door / 2 Shelf
CASTORS	Comes standard with 76mm castors and 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000005	FTE-120SDA-GN	\$4392.15



FTE-120SDA-GN COUNTER FREEZER



RTE-170SDA-GN COUNTER REFRIGERATOR



Product Specifications	
WEIGHT	Net: 103kg Gross: 115kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz / 1
AMPERAGE	1.4A
STARTING AMPERAGE	6.8A
DEFROST SYSTEM	Heater
TEMPERATURE CONTROL	Microprocessor controlled - adjustable from -6°C to 12°C
AMBIENT TEMPERATURE	5 - 43°C
EFFECTIVE CAPACITY	412L
REFRIGERANT	R134a
EXTERIOR	Stainless Steel, Galvanised Steel (Rear/Bottom)
INTERIOR	Stainless Steel, ABS Plastic
DOOR / SHELF	3 Door / 3 Shelf
CASTORS	Comes standard with 76mm castors and 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000008	RTE-170SDA-GN	\$4859.40




FTE-170SDA-GN COUNTER FREEZER



Product Specifications	
WEIGHT	Net: 109kg Gross: 121kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz / 1
AMPERAGE	3.4A
STARTING AMPERAGE	14.8A
DEFROST SYSTEM	Glass Tube Heater
TEMPERATURE CONTROL	Microprocessor controlled - adjustable from -25°C to -7°C
AMBIENT TEMPERATURE	5 - 43°C
EFFECTIVE CAPACITY	412L
REFRIGERANT	R404A
EXTERIOR	Stainless Steel, Galvanised Steel (Rear / Bottom)
INTERIOR	Stainless Steel, ABS Plastic
DOOR / SHELF	3 Door / 3 Shelf
CASTORS	Comes standard with 76mm castors and 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000006	FTE-170SDA-GN	\$5198.55

FTE-170SDA-GN COUNTER FREEZER



PROFESSIONAL UPRIGHT REACH IN REFRIGERATION & FREEZERS

Hoshizaki refrigeration and freezer products are designed for professional kitchens who demand a reliable easy to maintain product with a low cost of ownership.



Easy Cleaning

Removable door gaskets for easy cleaning without the need for tools.



Adjustable Shelves

The counter offers one height adjustable shelf per section as standard.



Hygienic Design

Dished stainless interior and base with rounded edges for easy cleaning.



User friendly controller

Control panel with digital thermometer / thermostat for accurate control and easy reading. A transparent plastic cover protects against accidental adjustment of temperature and fluid spillage.



Easy Service*

A compact slide out refrigeration unit for easy maintenance and service access.



HRE-70B UPRIGHT REACH IN REFRIGERATOR




Product Specifications	
WEIGHT	Net: 116kg / Packed: 131kg
AC SUPPLY VOLTAGE	220 - 240v / 50Hz / 1
ELECTRIC CIRCUIT PROTECTION	Earth Wire, Circuit Breaker
INTERIOR / EXTERIOR	Stainless Steel / Stainless Steel, Galvanized Steel (Rear, Bottom)
AMPERAGE	2.06A
REFRIGERATION SYSTEM	Forced Air Circulation Interior Fan - DC12V 4W x 1
DEFROST SYSTEM	Off-Cycle
TEMPERATURE CONTROL	Microprocessor (Digital temp. indication) - Adjustable from 0°C to 16°C
DEFROST CONTROL	Microprocessor
DRAIN EVAPORATOR PAN	Stainless steel, 170W
CASTOR	Urethane (76mm DIA, 115mm High)
EFFECTIVE CAPACITY	Approx. 631L
INSULATION	Polyurethane foam
REFRIGERANT	R134a
HEAT REJECTION	535W at 43°C ambient
AMBIENT TEMPERATURE	5 — 43°C

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000001	HRE-70B	\$4520.25



HRE-70B UPRIGHT REACH IN REFRIGERATOR



HFE-70B UPRIGHT FREEZER




Product Specifications	
WEIGHT	Net: 116kg / Packed: 131kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz / 1
ELECTRIC CIRCUIT PROTECTION	Earth Wire, Circuit Breaker
INTERIOR / EXTERIOR	Stainless Steel / Stainless Steel, Galvanized Steel (Rear, Bottom)
AMPERAGE	3.51A
REFRIGERATION SYSTEM	Forced Air Circulation Interior Fan - DC12V 4W x 2
DEFROST SYSTEM	Heater
TEMPERATURE CONTROL	Microprocessor (Digital temp. indication) - Adjustable from -25°C to -7°C
DEFROST CONTROL	Microprocessor
DRAIN EVAPORATOR PAN	Stainless Steel, 170W
CASTOR	Urethane (76mm DIA, 115mm High)
EFFECTIVE CAPACITY	Approx. 631L
INSULATION	Polyurethane Foam
REFRIGERANT	R404A
HEAT REJECTION	735W at 43°C ambient
AMBIENT TEMPERATURE	5 - 43°C

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000003	HFE-70B	\$5570.25



HFE-70B UPRIGHT FREEZER



HRE-140B UPRIGHT REACH IN REFRIGERATOR




Product Specifications	
WEIGHT	Net: 164kg Packed: 189kg
AC SUPPLY VOLTAGE	220 - 240v / 50Hz / 1
ELECTRIC CIRCUIT PROTECTION	Earth Wire, Circuit Breaker
INTERIOR / EXTERIOR	Stainless Steel / Stainless Steel, Galvanized Steel (Rear, Bottom)
AMPERAGE	2.89A
REFRIGERATION SYSTEM	Forced Air Circulation Interior Fan - DC12V 4W x 1
DEFROST SYSTEM	Off-Cycle
TEMPERATURE CONTROL	Microprocessor (Digital temp. indication) - Adjustable from 0°C to 16°C
DEFROST CONTROL	Microprocessor
DRAIN EVAPORATOR PAN	Stainless steel, 170W
CASTOR	Urethane (76mm DIA, 115mm High)
EFFECTIVE CAPACITY	Approx. 1379L
INSULATION	Polyurethane foam
REFRIGERANT	R134a
HEAT REJECTION	940W at 43°C ambient
AMBIENT TEMPERATURE	5 — 43°C

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000002	HRE-140B	\$6615.00



HRE-140B UPRIGHT REACH IN REFRIGERATOR



HFE-140B UPRIGHT REACH IN FREEZER




Product Specifications	
WEIGHT	Net: 174kg Packed: 199kg
AC SUPPLY VOLTAGE	220 - 240V / 50Hz / 1
ELECTRIC CIRCUIT PROTECTION	Earth Wire, Circuit Breaker
INTERIOR / EXTERIOR	Stainless Steel / Stainless Steel, Galvanized Steel (Rear, Bottom)
AMPERAGE	3.79A
REFRIGERATION SYSTEM	Forced Air Circulation Interior Fan - DC12V 4W x 3
DEFROST SYSTEM	Heater
TEMPERATURE CONTROL	Microprocessor (Digital temp. indication) - Adjustable from -25°C to -7°C
DEFROST CONTROL	Microprocessor
DRAIN EVAPORATOR PAN	Stainless Steel, 170W
CASTOR	Urethane (76mm DIA, 115mm High)
EFFECTIVE CAPACITY	Approx 1372L
INSULATION	Polyurethane Foam
REFRIGERANT	R404A
HEAT REJECTION	1330W
AMBIENT TEMPERATURE	5 - 43°C

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000004	HFE-140B	\$7828.80



HFE-140B UPRIGHT REACH IN FREEZER





COMMERCIAL SERIES REFRIGERATION & FREEZERS



Invention & Reliability in Foodservice Equipment

www.hoshizaki.com.au

COMMERCIAL SERIES REFRIGERATION & FREEZERS

The Hoshizaki Commercial series of refrigerators and freezers are unsurpassed when it comes to reliability and value for money.

A high operating ambient temperature (43°C for upright cabinets & 38°C for counter cabinets) ensures that the Commercial series meets your demands in all conditions.

The Commercial series offer many features including:

- *Split ½ doors for the upright Refrigeration and Freezers.*
- *Food service size internal shelving systems that allow full interior usage.*
- *Fully programmable digital controller.*
- *HACCP approved.*

Available in a variety of sizes and styles to suit all needs, these cabinets are designed for everyday commercial kitchen usage.

So when it comes to refrigeration and freezers for your commercial kitchen, think **Hoshizaki Commercial**.



COMMERCIAL COUNTER SERIES REFRIGERATION & FREEZERS

Hoshizaki refrigeration and freezer products are designed for professional kitchens who demand a reliable easy to maintain product with a low cost of ownership.



Easy Cleaning

Removable door gaskets for easy cleaning without the need for tools.



Adjustable Shelves

The counter offers 2 per door on counter cabinets (includes bottom shelf).



Hygienic Design

Dished stainless interior and base with rounded edges for easy cleaning.



User friendly controller

Control panel with digital thermometer / thermostat for accurate control and easy reading. A transparent plastic cover protects against accidental adjustment of temperature and fluid spillage.



Easy Maintenance

Easy access to front loaded air filter for cleaning.


RTC-120MDA COUNTER REFRIGERATOR



Product Specifications	
Weight	Net: 73kg Gross: 78kg
AC Supply Voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration System	Forced air circulation
Defrost System	Off cycle
Drain Evaporator Pan	Fin & Tube type
Temperature control	Microprocessor adj 0°C - 12°C
Effective capacity	307L
Refrigerant	R134a
door / shelf	2 doors / 4 shelves
Heat rejection	350W
Ambient Temperature	5°C - 38°C
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000055	RTC-120-MDA	\$3503.97

RTC-120MDA COUNTER REFRIGERATOR



RTC-120MNA COUNTER REFRIGERATOR




Product Specifications	
Weight	Net: 67kg Gross: 72kg
AC supply voltage	200 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration System	Forced air circulation
Defrost System	Off cycle
Temperature control	Microprocessor adjustable from 0°C to 12°C
Drain Evaporator Pan	Fin & Tube type
Effective capacity	231L
Refrigerant	R134a
Door / Shelf	2 Door / 4 Shelves
Heat Rejection	350W
Ambient Temperature	5°C - 38°C
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000050	RTC-120-MNA	\$3461.79



RTC-120MNA COUNTER REFRIGERATOR



FTC-120MDA COUNTER FREEZER




Product Specifications	
Weight	Net: 78kg Gross: 83kg
AC Supply Voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration system	Forced air circulation
Defrost System	Glass Tube Heater
Temperature Control	Microprocessor adjustable from -23°C to -7°C
Drain Evaporator Pan	Fin & Tube type
Effective Capacity	307L
Refrigerant	R404a
Door / shelf	2 Doors / 4 Shelves
Heat Rejection	650W
Ambient Temperature	5°C - 38°C
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000155	FTC-120-MDA	\$3627.91



FTC-120MDA COUNTER FREEZER



FTC-120MNA COUNTER FREEZER




Product Specifications	
Weight	Net: 72kg Gross: 77kg
AC supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration System	Forced air circulation
Defrost system	Glass Tube Heater
Temperature control	Microprocessor adjustable from -23°C to -7°C
Drain evaporator pan	Fin & Tube type
Effective capacity	231L
Refrigerant	R404a
Door / shelf	2 Door / 4 Shelves
Heat rejection	650W
Ambient Temperature	5 - 38°C
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000150	FTC-120-MNA	\$3498.17



FTC-120MNA COUNTER FREEZER



RTC-150MDA COUNTER REFRIGERATOR




Product Specifications	
Weight	Net: 87kg Gross: 92kg
AC Supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration System	Forced air circulation
Defrost System	Off cycle
Temperature control	Microprocessor adjustable from 0°C to 12°C
Drain evaporator pan	Fin & Tube type
Effective capacity	420L
Refrigerant	R134a
Door / Shelf	2 doors / 4 shelves
Heat rejection	360W
Ambient temperature	5°C - 38°C
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000056	RTC-150-MDA	\$4015.61



RTC-150MDA COUNTER REFRIGERATOR



RTC-150MNA COUNTER REFRIGERATOR




Product Specifications	
Weight	Net: 80kg Gross: 85kg
AC supply voltage	220 - 240°C / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration System	Forced air circulation
Defrost System	Off cycle
Temperature control	Microprocessor adjustable from 0°C to 12°C
Drain evaporator pan	Fin & Tube type
Effective capacity	318L
Refrigerant	R134a
Door / Shelf	2 door / 4 shelves
Ambient temperature	5 - 38°C
Heat Rejection	360W
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000051	RTC-150-MNA	\$3846.82



RTC-150MNA COUNTER REFRIGERATOR



FTC-150MDA COUNTER FREEZER




Product Specifications	
Weight	Net: 93kg Gross: 98kg
AC supply voltage	220 - 240V / 50Hz
Amperage	10A
Refrigeration system	Forced air circulation
Defrost system	Glass tube heater
Temperature control	Microprocessor adjustable from -23°C to -7°C
Drain evaporator pan	Fin & Tube type
Effective capacity	420L
Refrigerant	R404a
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Door / Shelf	2 Doors / 4 Shelves
Heat rejection	704W
Ambient temperature	5 - 38°C
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000156	FTC-150-MDA	\$4100.51



FTC-150MDA COUNTER FREEZER



FTC-150MNA COUNTER FREEZER




Product Specifications	
Weight	Net: 86kg Gross: 91kg
AC supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration system	Forced air circulation
Defrost System	Glass tube heater
Temperature control	Microprocessor adjustable from -23°C to -7°C
Drain evaporator pan	Fin & Tube type
Effective capacity	318L
Refrigerant	R404a
Door / Shelf	2 Doors / 4 Shelves
Ambient temperature	5 - 38°C
Heat rejection	650W
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000151	FTC-150-MNA	\$3884.25



FTC-150MNA COUNTER FREEZER



RTC-180MDA COUNTER REFRIGERATOR



Product Specifications	
Weight	Net: 101kg Gross: 107kg
Ac supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration system	Forced air circulation
Defrost System	Off cycle
Temperature control	Microprocessor adjustable from 0°C to 12°C
Drain evaporator pan	Fin & Tube type
Effective capacity	530L
Refrigerant	R134a
Door / Shelf	3 doors / 6 shelves
Ambient temperature	5 - 83°C
Heat rejection	380W
Castors	Comes standard with 76mm castors = 155mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000057	RTC-180-MDA	\$4094.74



Technical drawings of the refrigerator, including a top view, a side view, and a front view. The top view shows the overall dimensions and internal layout, including the evaporator, shelf, and air outlet duct. The side view shows the height and width of the unit. The front view shows the front panel, air filter, and digital thermometer. Dimensions are given in millimeters.

RTC-180MNA COUNTER REFRIGERATOR




Product Specifications	
Weight	Net: 93kg Gross: 99kg
Ac supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration system	Forced air circulation
Defrost System	Off cycle
Temperature control	Microprocessor adjustable from 0°C to 12°C
Drain evaporator pan	Fin & Tube type
Effective capacity	401L
Refrigerant	R134a
Door / Shelf	3 doors / 6 shelves
Heat rejection	380W
Ambient temperature	5 - 38°C
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000052	RTC-180-MNA	\$4041.97



RTC-180MNA COUNTER REFRIGERATOR



FTC-180MDA COUNTER FREEZER




Product Specifications	
Weight	Net: 107kg Gross: 113kg
Ac supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration system	Forced air circulation
Defrost system	Glass tube heater
Temperature control	Microprocessor adjustable from -23 to -7°C
Drain evaporator pan	Fin & Tube type
Effective capacity	530L
Refrigerant	R404a
Door / Shelf	3 doors / 6 shelves
Heat rejection	1083W
Ambient temperature	5 - 38°C
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
9700157	FTC-180-MDA	\$4347.91



FTC-180MDA COUNTER FREEZER



FTC-180MNA COUNTER FREEZER



Product Specifications	
Weight	Net: 99kg Gross: 105kg
AC supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration system	Forced air circulation
Defrost system	Glass tube heater
Temperature control	Microprocessor controlled adjustable from -23°C to -7°C
Drain evaporator pan	Fin & Tube type
Effective capacity	401L
Refrigerant	R404a
Door / Shelf	3 doors / 6 shelves
Ambient temperature	5 - 38°C
Heat rejection	704W
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000152	FTC-180-MNA	\$4053.04



POWER CORD 2300 LONG OUTSIDE (PLUG WITH EARTH WIRE)

VIEW A

DRAIN (OUTSIDE DIAMETER=18)

AIR

3.3

1800

112

600

458

230

DIGITAL THERMOMETER

FRONT PANEL

AIR FILTER

320

1410

70

100

24

638

700

800

40

310

1490

1440

50

100

210

58

104

208

420

420

420

45.3

495

45.3

436

540

50

4.7

525

15

EVAPORATOR

EFFECTIVE WIDTH 403

EFFECTIVE WIDTH 412

EFFECTIVE WIDTH 383

488

488

458

18

10

25

600

3

431

60

106

AIR OUTLET DUCT

571

599

55

51

A

COMMERCIAL SERIES UPRIGHT REACH IN REFRIGERATION & FREEZERS

Hoshizaki refrigeration and freezer products are designed for professional kitchens who demand a reliable easy to maintain product with a low cost of ownership.



Easy Cleaning

Removable door gaskets for easy cleaning without the need for tools.



Adjustable Shelves

The counter offers 4 per door on upright cabinets (includes bottom shelf).



Hygienic Design

Dished stainless interior and base with rounded edges for easy cleaning.



User friendly controller

Control panel with digital thermometer / thermostat for accurate control and easy reading. A transparent plastic cover protects against accidental adjustment of temperature and fluid spillage.



Easy Maintenance

Conveniently located air filters on all cabinets.




HRE-77MA UPRIGHT REFRIGERATOR



Product Specifications	
Weight	Net: 98kg Gross: 120kg
Ac Supply Voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration System	Forced Air Circulation
Defrost System	Off Cycle
Temperature control	Microprocessor adjustable from -2°C to 12°C
Drain Evaporator Pan	Fin & Tube type
Effective capacity	546L
Refrigerant	R134a
Heat Rejection	410W
Ambient temperature	5°C to 43°C
Castors	Comes standard with Urethane 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000030	HRE-77-MA	\$3472.32

HRE-77MA UPRIGHT REFRIGERATOR



HFE-77MA UPRIGHT FREEZER




Product Specifications	
Weight	Net: 102kg Gross: 124kg
Ac supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration System	Forced Air Circulation
Defrost system	Heater
Temperature control	Microprocessor adjustable from -23°C to -7°C
Drain Evaporator Pan	Fin & Tube type
Castor	Urethane (76mm DIA, 115mm High)
Effective capacity	546L
Refrigerant	R404a
Heat Rejection	670W
Ambient temperature	5°C to 43°C
Castors	Comes standard with Urethane 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000130	HFE-77-MA	\$3683.29



HFE-77MA UPRIGHT FREEZER



HRE-127MA UPRIGHT REFRIGERATOR



Product Specifications	
Weight	Net: 141kg Gross: 172kg
Ac Supply Voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration system	Forced air circulation
Defrost system	Off cycle
Temperature control	Microprocessor adjustable from -2°C to 12°C
Drain Evaporator Pan	Fin & Tube type
Effective capacity	1080L
Refrigerant	R134a
Heat Rejection	560W
Ambient Temperature	5°C to 43°C
Castors	Comes standard with Urethane 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000031	HRE-127-MA	\$4648.56





HFE-127MA UPRIGHT FREEZER




Product Specifications	
Weight	Net: 146kg Gross: 177kg
Ac Supply voltage	220 - 240V / 50Hz
Interior / exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration System	Forced air circulation
Defrost System	Heater
Temperature control	Microprocessor adjustable from -23°C to -7°C
Drain Evaporator Pan	Fin & Tube type
Effective capacity	1070L
Refrigerant	R404a
Heat Rejection	1030W
Ambient temperature	5°C - 43°C
Castors	Comes standard with 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000131	HFE-127-MA	\$5123.26



HFE-127MA UPRIGHT FREEZER



HRE-147MA UPRIGHT REFRIGERATOR







Product Specifications	
Weight	Net: 159kg Gross: 193kg
Ac Supply voltage	220-240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration System	Forced Air Circulation
Defrost System	Off cycle
Temperature control	Microprocessor adjustable from -2°C 12°C
Drain Evaporator Pan	Fin & Tube type
Effective capacity	1217L
Refrigerant	R134a
Heat rejection	610W
Ambient temperature	5°C - 43°C
Castors	Comes standard with Urethane 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000032	HRE-147-MA	\$5423.94



HRE-147MA UPRIGHT REFRIGERATOR




HFE-147MA UPRIGHT FREEZER



Product Specifications	
Weight	Net: 164kg Gross: 198kg
AC supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration System	Forced Air circulation
Defrost System	Heater
Temperature control	Microprocessor adjustable -23°C to -7°C
Drain Evaporator Pan	Fin & Tube type
Effective capacity	1203L
Refrigerant	R404a
Heat Rejection	1150W
Ambient Temperature	5°C - 43°C
Castors	Comes standard with Urethane 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000132	HFE-147-MA	\$5903.91

HFE-147MA UPRIGHT FREEZER







HRE-187MA UPRIGHT REFRIGERATOR



Product Specifications	
Weight	Net: 184kg Gross: 226kg
Ac supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration system	Forced air circulation
Defrost system	Off cycle
Temperature control	Microprocessor adjustable from -2°C to 12°C
Drain Evaporator Fan	Fin & Tube type
Effective capacity	1600L
Refrigerant	R134a
Heat Rejection	790W
Ambient Temperature	5°C - 43°C
Castors	Comes standard with Urethane 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000033	HRE-187-MA	\$6399.74

HRE-187MA UPRIGHT REFRIGERATOR



HFE-187MA UPRIGHT FREEZER



Product Specifications	
Weight	Net: 196kg Gross: 238kg
AC Supply voltage	220 - 240V / 50Hz
Interior / Exterior	Stainless steel (ABS plastic interior doors)
Amperage	10A
Refrigeration system	Forced air circulation
Defrost system	Heater
Temperature control	Microprocessor adjustable from -23°C to -7°C
Drain evaporator fan	Fin & Tube type
Effective capacity	1600L
Refrigerant	R404a
Heat Rejection	1210W
Ambient temperature	5°C - 43°C
Castors	Comes standard with Urethane 76mm castors = 115mm floor clearance

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000133	HFE-187-MA	\$6914.00

Technical drawing of the rack assembly showing dimensions and components. The drawing includes labels for 'DEAN EXHAUSTING TANK', 'AIR', 'RACK ADJUSTMENT, PITCHED AT 25mm', and 'BOTTOM SHELF'. Dimensions are provided in millimeters (mm) and inches (in).

Dimensions (mm):

- 88
- 892
- 1462
- 892
- 88
- 1484

Dimensions (in):

- 3.5
- 35.1
- 57.5
- 35.1
- 3.5
- 58.4



EURO LINE REFRIGERATION & FREEZERS



Invention & Reliability in Foodservice Equipment

www.hoshizaki.com.au

EURO LINE REFRIGERATION & FREEZERS

Welcome to the world of Hoshizaki Euro Line Refrigeration and Freezer equipment.

A bold, stylish and functional range of Refrigeration and Freezers designed to suit your menus and kitchens.

Suitable for “front of house “ or “back of house” applications, the Hoshizaki Euro Line range offers;

- *2 year warranty (stc)*
- *Large range of styles and sizes (N.b. see below)*
- *Preparation, production, holding or display types of Refrigeration and Freezers*
- *Lockable, self-closing, solid and glass door options*
- *High grade heavy duty stainless steel construction*
- *Energy efficient motors and operating systems including auto “shut off” when doors are opened*
- *Long life LED and Halogen lighting systems (where available)*
- *Leg or Castor options to suit all projects*

(N.b. Hoshizaki Lancer stock a range of Hoshizaki Euro Line. Other equipment may need to be ordered in, please consult your local Hoshizaki Lancer Sales team.)

Researched, developed and manufactured from our own major European refrigeration factory; the Hoshizaki Euro Line range is renowned for reliability and durability. A respect gained over many years.

“When you need practicality and good looks in your business, go for Hoshizaki Euro Line”



HOSHIZAKI EURO LINE COUNTER REFRIGERATION & FREEZERS

Purchasing a Hoshizaki Preparation Bench shows your dedication to hygiene, working environment and the best modern refrigeration technology and design available.

Whether it is a 2, 3 or 4 door undercounter unit, whether it is a work, pizza or saladette preparation bench, all of the below features plus more are available with the Hoshizaki Euro Line undercounter series.



Hygiene

Stainless steel inside and out.
Bullnose edging on all units.
"Dished Pan" internals and rounded corners to allow ease of cleaning and HACCP compliance.



Working Environment

Anti - Tilt shelving and pull stops on drawers. Removable drawer and door gaskets.
Standard with 100mm castors.



Modern Refrigeration Technology and Design

Energy efficient motors and internal refrigeration systems. Intelligent, programmable digital controllers. Compact slide out refrigeration for ease of service.
Modular design for a full suite fit out.




COUNTER PREPARATION BENCH



<i>Product Specifications</i>	
<i>Weight</i>	Packed: 158kg
<i>AC Supply Voltage</i>	240V / 50 Hz
<i>Exterior / Interior</i>	Stainless / Stainless
<i>Amperage</i>	10A
<i>Refrigeration System</i>	Forced Air Circulation
<i>Temperature Control</i>	+2 / +12°C
<i>Effective Capacity</i>	397L
<i>Refrigerant</i>	R134a
<i>Door / Shelf</i>	1 Door / 1 Shelf / 2 stainless wire drawers / 2 drawer sections, one with 2 x 1/2 drawers and one with 3 x 1/3 drawers
<i>Ambient Temperature</i>	5 - 40°C
<i>Castors</i>	Comes standard with 127mm castors

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
97000221	Hoshizaki Euro Line Counter Preparation Bench	\$8306.00

COUNTER PREPARATION BENCH






PIZZA PREPARATION BENCH



Product Specifications	
Weight	Packed: 160kg
AC Supply Voltage	240V / 50Hz
Exterior / Interior	Stainless / Stainless
Amperage	10A
Refrigeration System	Forced Air Circulation
Temperature Control	+ 2 / +12°C
Effective capacity	397L
Refrigerant	R134a
Door / Shelf	3 door sections each with 2 stainless shelves
Ambient Temperature	5 - 40°C
Castors	Comes standard with 127mm castors

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000220	Hoshizaki Euro Line Pizza Preparation Bench	\$9468.00

PIZZA PREPARATION BENCH




SALADETTE PREPARATION BENCH



Product Specifications	
Weight	Packed: 158kg
AC Supply Voltage	240V / 50Hz
Exterior / Interior	Stainless / Stainless
Amperage	10A
Refrigeration System	Forced Air Circulation
Temperature Control	+2 / +12°C
Effective Capacity	397L
Refrigerant	R134a
Door / Shelf	3 Door sections each with 2 stainless shelves
Ambient Temperature	5 - 40°C
Castors	Comes standard with 127mm castors

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000222	Hoshizaki Euro Line Salad Preparation Bench	\$7474.00

SALADETTE PREPARATION BENCH



HOSHIZAKI EURO LINE UPRIGHT REFRIGERATION & FREEZERS

Innovative and functional food storage is what you get with Hoshizaki Euro Line upright refrigeration and freezers. Packed with features expected of a European built cabinet, the Hoshizaki Euro Line is "hot" when it comes to your chilling or freezing needs.

For stylish, practical refrigeration or freezer systems, the Hoshizaki Euro Line upright series offers more value and features for less dollars.

Unique Air Distribution system

- Ensures all your foods are chilled & protected wholly and evenly
- Uniform chilled or frozen air temperature throughout the cabinet
- Motor "Cut out" when the doors are opened to minimise temperature loss, increase efficiency and save on your power bills

Hygiene

- Stainless steel inside and out
- Rounded corners for ease of cleaning
- Easy access filters and motors for cleaning and maintenance

Digital Controllers

- Fully programmable and adjustable to suit your Food Safety programme
- Digital controller "lock out" feature
- Acoustic door alarms to maintain your HACCP compliance

Lighting

- Long lasting Halogen or LED lighting that can be operated via a separate switch to suit your needs




COMPACT 410 GLASS DOOR REFRIGERATOR



Product Specifications	
Weight	Packed: 84kg
AC Supply Voltage	240V / 50Hz
Exterior / Interior	Stainless or White / Stainless, White
Amperage	10A
Refrigeration System	Forced Air Circulation
Temperature Control	+2 / +12°C
Effective Capacity	312L
Refrigerant	R134a
Door / Shelf	1 Door / 6 Shelves
Ambient Temperature	5 - 40°C
Castors	Comes standard with 125mm castors

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000200	Hoshizaki Euro Line Compact 410 Glass Door Refrigerator Stainless Steel exterior	\$3592.00
97000201	Hoshizaki Euro Line Compact 410 Glass Door Refrigerator White exterior	\$3495.00

COMPACT 410 GLASS DOOR REFRIGERATOR




MIDI 425 GLASS DOOR REFRIGERATOR



Product Specifications	
Weight	Packed: 124kg
AC Supply Voltage	240V / 50Hz
Exterior / Interior	White / Stainless, White
Amperage	10A
Refrigeration System	Forced Air Circulation
Temperature Control	+2 / +12°C
Effective capacity	388L
Refrigerant	R134a
Door / Shelf	1 Door / 4 Shelves
Ambient Temperature	5 - 40°C
Castors	Comes standard with 20mm castors

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000202	Hoshizaki Euro Line Midi 425 Glass Door Refrigerator	\$7098.00

MIDI 425 GLASS DOOR REFRIGERATOR




MIDI 425 GLASS DOOR FREEZER



Product Specifications	
Weight	Packed: 127kg
AC Supply Voltage	240V / 50Hz
Amperage	10A
Refrigeration System	Forced Air Circulation
Temperature Control	-25 / - 5°C
Effective Capacity	388L
Refrigerant	R404a
Door / Shelf	1 Door / 4 Shelves
Ambient Temperature	5 - 40°C
Castors	Comes standard with 20mm castors

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000231	Hoshizaki Euro Line Midi 425 Glass Door Freezer	\$8085.00

MIDI 425 GLASS DOOR FREEZER




MIDI 625 GLASS DOOR REFRIGERATOR



<i>Product Specifications</i>	
<i>Weight</i>	Packed: 131kg
<i>AC Supply Voltage</i>	240V / 50Hz
<i>Exterior / Interior</i>	White / Stainless, White
<i>Amperage</i>	10A
<i>Refrigeration System</i>	Forced Air Circulation
<i>Temperature Control</i>	+2 / +12°C
<i>Effective capacity</i>	571L
<i>Refrigerant</i>	R134a
<i>Door / Shelf</i>	1 Door / 4 Shelves
<i>Ambient Temperature</i>	5 - 40°C
<i>Castors</i>	Comes standard with 20mm castors

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
97000203	Hoshizaki Euro Line Midi 625 Glass Door Refrigerator	\$7788.00

MIDI 625 GLASS DOOR REFRIGERATOR




MIDI 625 GLASS DOOR FREEZER



<i>Product Specifications</i>	
<i>Weight</i>	Packed: 138kg
<i>AC Supply Voltage</i>	240V / 50Hz
<i>Exterior / Interior</i>	White / Stainless, White
<i>Amperage</i>	10A
<i>Temperature Control</i>	-25 / -5°C
<i>Refrigerant</i>	R404a
<i>Door / Shelf</i>	1 Door / 4 Shelves
<i>Ambient Temperature</i>	5 - 40°C
<i>Castors</i>	Comes standard with 20mm castors

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
97000232	Hoshizaki Euro Line Midi 625 Glass Door Refrigerator	\$9492.00

MIDI 625 GLASS DOOR FREEZER





AHT IMPULSE COOLERS

green.freshness.worldwide **AHT** 

www.hoshizaki.com.au

AHT IMPULSE COOLERS

Cool dress for success – stylish designs that enhance sales & help build brand awareness. Our goal is to provide the perfect equipment to present your products in the market. AHT Beverage & Food Display Coolers offer the right temperature & conditions for your products like dairy, pre-packed sandwiches, salads or all kinds of beverages. The innovative & elegant appearance of AHT Display Coolers also guarantees that your product will be in the centre of your customer's attention.



AHT FANCY SLIM IMPULSE COOLER

green.freshness.worldwide **AHT**



Product Specifications

EXTERNAL DIMENSIONS	W x D x H (mm): 395 x 476 x 1850
INTERNAL DIMENSIONS	W x D x H (mm): 320 x 341 x 1400
VOLUME	134.5 Litre
PACKOUT	(330ml cans / 500ml bottles): 133 / 80 pieces
TEMPERATURE RANGE	0°C to 5°C (adjustable to -3°C)
REFRIGERANT	R134a
AMBIENT TEMPERATURE / HUMIDITY	Max 32°C / 65 RH
WEIGHT	Net: 60kg Gross: 69kg
LOADABILITY	20' / 40': 50 / 110 pieces

Product Range

PART NO.	DESCRIPTION	LIST PRICE
20000058	AHT Fancy Slim Impulse Cooler	

AHT 65 BC RC IMPULSE COOLER

green.freshness.worldwide **AHT**



Product Specifications	
EXTERNAL DIMENSIONS	W x D x H (mm): 548 x 960
INTERNAL DIMENSIONS	W x D x H (mm): 390 x 535
VOLUME	Net: 65L Gross: 77L
PACKOUT	73 cans (330ml)
TEMPERATURE RANGE	2°C to 10°C
REFRIGERANT	R134a
AMBIENT TEMPERATURE/HUMIDITY	32°C / 65 RH
WEIGHT	Net: 35kg Gross: 40kg
LOADABILITY	20' / 40': 80 / 160pcs

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
20000065	AHT 65 BC RC	



AHT AC SLIM IMPULSE COOLER

green.freshness.worldwide **AHT**



Product Specifications	
EXTERNAL DIMENSIONS	AC SLIM-170: 477 x 551 x 1700mm (WxDxH) AC SLIM-130: 500 x 517 x 1300mm (WxDxH)
INTERNAL DIMENSIONS	AC SLIM-170: 412 x 400 x 1044mm (WxDxH) AC SLIM-130: 430 x 384 x 712mm (WxDxH)
LIGHTING	LED (1 horizontal / 2 vertical)
PACKOUT	AC SLIM-170: approx. 120 cans(33cl) / 120 bottles (500ml) AC SLIM-130: approx. 200 (250ml) / 144 (330ml)
TEMPERATURE RANGE	AC SLIM-170: 2°C to 12°C AC SLIM-130: 2°C to 6°C
REFRIGERANT	R134a
AMBIENT TEMPERATURE/ HUMIDITY	AC SLIM-170: Max 22°C / 60 RH AC SLIM-130: Max 24°C / 55 RH
WEIGHT	AC SLIM-170: Net/Gross (kg) 75 / 97 AC SLIM-130: Net/Gross (kg) 68 / 72
LOADABILITY	AC SLIM-170: 20'/40'/13.6m pcs - 40/80/92 (tbc) AC SLIM-130: 20'/40'/13.6m pcs - 40/80/96

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
20000062	AC Slim - 170	
20000061	AC Slim - 130	



AHT AC S IMPULSE COOLER

green.freshness.worldwide **AHT**



Product Specifications

EXTERNAL DIMENSIONS	W x D x H (mm): 706 x 717 x 1495
INTERNAL DIMENSIONS	W x D x H (mm): 615 x 565 x 835
VOLUME	Net: 190L Gross: 245L
LIGHTING	2 x 14W vertical
SHELF DIMENSIONS	610 x 320 / 385
PACKOUT	270 cans (330ml)
TEMPERATURE RANGE	2°C TO 12°C (3M2)
REFRIGERANT	R404A / R290
AMBIENT TEMPERATURE/HUMIDITY	25°C / 60 RH
WEIGHT	Net: 114kg Gross: 132kg
LOADABILITY	20' / 40' / 13.6m: 21 / 45 / 51 pcs

Product Range

PART NO.	DESCRIPTION	LIST PRICE
20000080	AHT AC S	



AHT AC M IMPULSE COOLER

green.freshness.worldwide **AHT**



Product Specifications	
EXTERNAL DIMENSIONS	W x D x H (mm): 716 x 724 x 1972
INTERNAL DIMENSIONS	W x D x H (mm): 615 x 565 x 1350
VOLUME	Net: 324L Gross: 463L
LIGHTING	2 x 28W and 1 x 8W
SHELF DIMENSIONS	610 x 385mm
PACKOUT	(330ml cans / 500ml bottles): 468 / 225
TEMPERATURE RANGE	2°C to 12°C (3M2)
REFRIGERANT	R404A / R290
AMBIENT TEMPERATURE/HUMIDITY	25°C / 60 RH
WEIGHT	Net: 152kg Gross: 165kg
LOADABILITY	20' / 40' / 13.6m: 21 / 45 / 51 pcs

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
20000081	AHT AC M	



AHT AC XL IMPULSE COOLER

green.freshness.worldwide **AHT**



Product Specifications	
EXTERNAL DIMENSIONS	W x D x H (mm): 1195 x 882 x 1972
INTERNAL DIMENSIONS	W x D x H (mm): 1100 x 700 x 1290
VOLUME	Net: 770L Gross: 1060L
LIGHTING	2 x 21W and 2 x 28W
SHELF DIMENSIONS	1094 x 510
PACKOUT	(330ml cans/500ml bottles): 1224/560 pieces
TEMPERATURE RANGE	2°C to 12°C (3M2)
REFRIGERANT	R404A
AMBIENT TEMPERATURE/ HUMIDITY	25°C / 60 RH
WEIGHT	Net: 227kg Gross: 255kg
LOADABILITY	20' / 40' / 13.6m: 10 / 21 / 24 pcs

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
20000082	AHT AC XL	





SUSHI CABINETS



Invention & Reliability in Foodservice Equipment

www.hoshizaki.com.au

SUSHI CABINETS

With rounded glass windows and black exterior Hoshizaki sushi cases provide an eye catching point of sales display to attract customers.

SUSHI PRODUCT HIGHLIGHTS

Hoshizaki's HNC Sushi Cabinets are designed to be aesthetically appealing. They are produced to sit on counter tops, with a contemporary and modern design that looks great as well keeping your sushi cooled at exactly the right temperature.



- Stable humidity and temperature levels are maintained at all times, instead of forced air circulation methods that dry out and ruin displayed sushi. Your sushi will stay fresh longer and taste as good as it looks.
- Hoshizaki machines will not defrost and allow condensation to drip onto the sushi displayed within them, protecting the integrity of the product at all times.
- 12 month warranty on all Hoshizaki sushi cabinets.



HNC-120BE-L COUNTER SHOWCASE




<i>Product Specifications</i>	
<i>EXTERIOR DIMENSIONS</i>	Width: 1200mm Depth: 345mm Height: 270mm
<i>INTERIOR DIMENSIONS</i>	Width: 845mm Depth: 288mm (floor) Height: 157mm
<i>WEIGHT</i>	Net: 32kg Packed: 44kg
<i>AC SUPPLY VOLTAGE</i>	220 - 240V / 50Hz 10Amps
<i>RATED AMPERAGE</i>	1.1A
<i>SATURATION TEMPERATURE</i>	Approx 4°C (Ambient temp 27°C, no load)
<i>NET CAPACITY</i>	42litres
<i>AMBIENT TEMPERATURE</i>	10°C - 30°C
<i>REFRIGERATION SYSTEM</i>	Convection Cooling

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
91000034	HNC-120BE-L	\$3568.95



HNC-120BE-L COUNTER SHOWCASE



HNC-150BE-L COUNTER SHOWCASE




<i>Product Specifications</i>	
<i>EXTERIOR DIMENSIONS</i>	Width: 1500mm Depth: 345mm Height: 270mm
<i>INTERIOR DIMENSIONS</i>	Width: 1145mm Depth: 288mm (floor) Height: 157mm
<i>WEIGHT</i>	Net: 37kg Packed: 52kg
<i>AC SUPPLY VOLTAGE</i>	220 - 240V / 50Hz 10Amps
<i>RATED AMPERAGE</i>	1.1A
<i>SATURATION TEMPERATURE</i>	Approx 4°C (Ambient temp 30°C, no load)
<i>NET CAPACITY</i>	57litres
<i>AMBIENT TEMPERATURE</i>	10°C - 30°C
<i>REFRIGERATION SYSTEM</i>	Convection Cooling

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
91000035	HNC-150BE-L	\$3808.35



HNC-150BE-L COUNTER SHOWCASE



HNC-180BE-R-B COUNTER SHOWCASE




<i>Product Specifications</i>	
<i>EXTERIOR DIMENSIONS</i>	Width: 1800mm Depth: 345mm Height: 270mm
<i>INTERIOR DIMENSIONS</i>	Width: 1445mm Depth: 288mm (floor) Height: 157mm
<i>WEIGHT</i>	Net: 42kg Packed: 60kg
<i>AC SUPPLY VOLTAGE</i>	220 - 240V / 50Hz 10Amps
<i>SATURATION TEMPERATURE</i>	Approx 4°C (Ambient temp 27°C, no load)
<i>NET CAPACITY</i>	72L
<i>AMBIENT TEMPERATURE</i>	10°C - 30°C
<i>REFRIGERATION SYSTEM</i>	Convection Cooling

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
91000037	HNC-180BE-R-B	\$4055.10



HNC-180BE-R-B COUNTER SHOWCASE




HNC-210BE-R-B COUNTER SHOWCASE



<i>Product Specifications</i>	
<i>EXTERIOR DIMENSIONS</i>	Width: 2100mm Depth: 345mm Height: 270mm
<i>INTERIOR DIMENSIONS</i>	Width: 1745mm Depth: 288mm (floor) Height: 157mm
<i>WEIGHT</i>	Net: 47kg Packed: 68kg
<i>AC SUPPLY VOLTAGE</i>	220 - 240V / 50Hz 10Amps
<i>RATED AMPERAGE</i>	1.1A
<i>SATURATION TEMPERATURE</i>	Approx 4°C (Ambient temp 27°C, no load)
<i>NET CAPACITY</i>	87L
<i>AMBIENT TEMPERATURE</i>	10°C - 30°C
<i>REFRIGERATION SYSTEM</i>	Convection Cooling

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
91000041	HNC-210BE-R-B	\$4275.60

HNC-210BE-R-B COUNTER SHOWCASE



HOSHIZAKI SPARE PARTS

National Ice Parts is our authorised Hoshizaki genuine factory parts supplier for Australia.

Contact them for all your parts requirements for Hoshizaki ice machines and refrigerators.

TOLL FREE NUMBER - 1800 206 235

PH: 02 8677 0222

FAX: 02 8677 9978

EMAIL: INFO@NATIONALICEPARTS.COM.AU

ADDRESS: UNIT 7, 2 RICHARD CLOSE, NORTH ROCKS NSW 2151

WEBSITE: WWW.NATIONALICEPARTS.COM.AU



ACCREDITATION AND TERMS

ACCREDITATIONS

HACCP

- Hazard Analysis Critical Control Point (HACCP) is the main platform for International legislation and good manufacturing practices for all sectors of the food industry.
- HACCP also forms a key component of many certified compliance standards and is recognized as a main element of international trade in food products.
- HACCP is a risk management tool recognized internationally for use in the pro active management of food safety issues.



WATERMARK

The WaterMark Code requires that plumbing and drainage products must have a WaterMark certification. Without this certification, they cannot be legally installed in accordance with Australian State and Territory plumbing legislation.

A WaterMark licence confirms that the product complies with the requirements of the Plumbing Code of Australia and the specifications listed in relevant Australian Standards. The specifications relate to the quality of the product, including aspects of health and safety, and warrant that it is fit for purpose. Use of the WaterMark is not limited to goods manufactured in Australia; it may be used on goods imported into Australia.



State, territory and local governments collectively ensure compliance with the Plumbing Code, including the requirement that only WaterMarked products are installed. Plumbers are required to meet the appropriate standards under their licence, with inspections carried out on building sites, mainly in relation to new buildings, by plumbing regulators.

Australian consumers can be confident about the quality of plumbing and draining products certified with the WaterMark.

TERMS

Refer to our full Terms and Conditions on our website: <http://lancerbeverage.com/footer/terms-and-conditions/terms-and-conditions>

The prices in this catalogue are to be used as a guide only; they do not incorporate all Hoshizaki Lancer products. All prices are GST exclusive. For information on any products not listed, please contact your local branch. Descriptions and specifications are subject to change at any time, without notice. Illustrations for demonstration purposes only. Elements of the pictures shown within this catalogue may not be standard and could incur additional charges.

For warranties please refer to the product pages on our website.

Copyright © 2014 Hoshizaki Lancer Pty Ltd All rights reserved. E&OE.





Invention & Reliability in Foodservice Equipment

HOSHIZAKI LANCER

PO Box 331 Welland SA 5007

5 Toogood Avenue Beverley SA 5009

T+ 61 8 8268 1388

F+ 61 8 8268 1978

info@hoshizaki.com.au

www.hoshizaki.com.au

6 Jul 2015