

One Glass Door Bottom Mount Upright Fridge

Range: BME
SKOPE ID: SM60GYA
Dimensions: 740 mm (W) × 795 mm (D) × 2005 mm (H)
Capacity: 559 L

Project: _____

Item #: _____



A high-efficiency, bottom-mounted, heavy duty, 1-door display fridge suitable for front and back-of-house applications including restaurants, cafés, clubs, pubs, bars, quick service restaurants, and more. Made from powder-coated, galvanised steel, the cabinet comes complete with four adjustable height wire shelves and one stainless steel fixed shelf, easily adjustable via SKOPE's unique ezi-clip and numbered shelf supports. The "frameless" glass door provides maximum product viewing and is designed for condensation protection via the double-glazed, argon-filled, low-e, insulated panels. The high impact built-in LED lights can be timed to turn on and off according to your opening times via the free SKOPE-connect smartphone app. With M1 compliance, the fridge is engineered to store food and drinks at a standard 1°C to 4°C (adjustable up to 15°C). This high-performance model is the most energy efficient on the market, and is certified under GEMS to the mandatory climate class 3 and is fully tested to operate in ambient environments of up to 40°C (climate class 5). The fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge, and low noise output. The bottom-mounted, fully removable, modular refrigeration cartridge can be easily removed in line with best practice for safe servicing of flammable refrigerants. With the same cartridge being used in both top and bottom-mounted fridges from 600 L to 1000 L, you achieve the fastest possible servicing times with minimal business disruption. The fridge includes a smart controller that connects to the free SKOPE-connect app, enabling you to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty



ActiveCore Technology




Natural Refrigerant



GEMS



SKOPE-connect



Cabinet

Type	ActiveCore	
Finish	Powder-coated galvanised steel	
Insulation	Type	PU foam
	Thickness (mm)	50
Doors	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)
	Type	Glass swing door (double-glazed, single low-e, argon-filled, toughened, safety glass), tab-locking
Shelving	Opening Size	Height (mm) 1455 Width (mm) 620
		Five shelves 4 × adjustable height shelf (625W × 520D), 1 × fixed bottom shelf (625W × 515D)
Lighting	Sign	n.a.
	Interior*	1 × 1370 mm, 15 W LED

Dimensions†

	External	Internal	Packed
Width (mm)	740	640	760
Depth (mm)	795	600	790
Height (mm)	2005 (castors)	1455	2220
Weight (kg)	156		159
Capacity (L)	559		
Footprint (m²)	0.59		

Ventilation (mm)

Top	Sides	Rear
50	Not required	50

Product Loading

	330 ml can	600 ml bottle
Facing	45	40
Loading	315	280

Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet		Multiple cabinets	
			At each joint	At each end wall
Less than 1 metre	±5 mm		±5 mm	+15 mm
More than 1 metre	-5 mm to +10 mm		-5 mm to +10 mm	+15 mm

Performance

Product Temperature Range (°C)	1 to 4 (adjustable* from 1 to 15)
Maximum Ambient Temperature (°C)	40
Sound Power Level (dB(A))	61.2

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	10
Product Temperature Class	M1 (-1 to 5°C)
Total Energy Consumption	1.60 kWh/24 h
Annual Running Costs	\$175 (@ \$0.30/kWh)

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	2 m power cord with 3-pin, 10 amp plug
Current draw (A)	1.6

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)		
System Type	Removable cartridge		
Cartridge Weight (kg)	26.5		
Refrigerant/Charge	R290/111 g		
Nominal Capacity (W)	547		
Heat Rejection (W)	Average	75	Peak 95
Defrost Type	Automatic, off-cycle		
Drainage	No plumbing required		

* Accessible via the free SKOPE-connect™ app.



BME600N-A
on the SKOPE website