

Camshelving® Elements Series

4-Shelf Starter Units for Stationary Units Vented Shelf Plates with Camguard® Antimicrobial

3 Post Heights

64" (1630 mm), 72" (1830 mm),
84" (2140 mm)

3 Shelf Depths

18" (460 mm), 21" (540 mm), 24" (610 mm)

5 Shelf Lengths

36" (910 mm), 42" (1070 mm), 48" (1220 mm),
54" (1380 mm), 60" (1530 mm)



* Starter Unit Includes:

4 stationary posts with leveling feet installed pre-assembled with post connectors and wedges, 1 bag of 32 stationary traverse dovetails (16 ea. A and B), vented shelf plates (for 4 shelves), 8 stationary traverses and instructions.

Features & Benefits

Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up 48" (1220 mm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" – 78" (1380 mm – 1980 mm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold up to 400 lbs. (182 kg) on a 36" (910 mm) to 48" (1220 mm) traverse.

Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

Shelving for Life

Non-corrosive design will endure all areas of operation – dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings – without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

Fits in Any Space

Innovative design helps maximize valuable space and provides strength and stability. Straight line components are attached by sharing posts of existing units with no loss of weight-bearing capacity. Corner Connectors bring units together in 90° angle to create corner & U-shaped units. Reduces costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

Item No. _____


Specifier Identification No. _____

Model No. _____

Quantity _____



Four Shelf Unit with Vented Shelf Plates.



Dunnage Stand
Recommended for Units
54" (1380 mm) or longer.



Set of Left and Right Corner Connectors
(1 set required per shelf).

Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece dovetails secure Traverses so they can be set easily into place.

Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Adjustable foot on bottom of each stationary Post adjusts easily for floor irregularities so shelf contents are securely stored and leveled.

Optional Accessories

Wall Fastener and Seismic Foot are packed 4 per case and do not include bolts or screws. Identification Tags clip easily onto traverses.

Approvals



COMPONENT

* Does not include Wall Fastener and Seismic Foot.

Camshelving® Elements Series

4-Shelf Starter Units for Stationary Units Vented Shelf Plates with Camguard® Antimicrobial

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____

Four shelf Starter Unit

CODE	TRAVERSE IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
64" (1630 mm) Height 18" (460 mm) Depth			
ESU183664V4	36" 910 mm	49.99 (5.92)	22,68 (0,17)
ESU184264V4	42" 1070 mm	54.53 (5.92)	24,74 (0,17)
ESU184864V4	48" 1220 mm	58.94 (5.92)	26,74 (0,17)
ESU185464V4	54" 1380 mm	63.64 (5.92)	28,87 (0,17)
ESU186064V4	60" 1530 mm	68.26 (5.92)	30,96 (0,17)
64" (1630 mm) Height 21" (540 mm) Depth			
ESU213664V4	36" 910 mm	54.94 (7.39)	24,92 (0,21)
ESU214264V4	42" 1070 mm	60.23 (7.39)	27,32 (0,21)
ESU214864V4	48" 1220 mm	65.28 (7.39)	29,61 (0,21)
ESU215464V4	54" 1380 mm	70.74 (7.39)	32,09 (0,21)
ESU216064V4	60" 1530 mm	76.11 (7.39)	34,52 (0,21)
64" (1630 mm) Height 24" (610 mm) Depth			
ESU243664V4	36" 910 mm	59.50 (8.49)	26,99 (0,24)
ESU244264V4	42" 1070 mm	61.66 (8.49)	27,97 (0,24)
ESU244864V4	48" 1220 mm	71.72 (8.49)	32,53 (0,24)
ESU285464V4	54" 1380 mm	77.70 (8.49)	35,24 (0,24)
ESU246064V4	60" 1530 mm	83.59 (8.49)	37,92 (0,24)
84" (2140 mm) Height 24" (610 mm) Depth			
ESU243684V4	36" 910 mm	61.46 (14.30)	27,88 (0,14)
ESU244284V4	42" 1070 mm	67.27 (15.57)	30,51 (0,17)
ESU244884V4	48" 1220 mm	73.68 (12.57)	33,42 (0,16)
ESU245484V4	54" 1380 mm	80.66 (14.59)	36,58 (0,20)
ESU246084V4	60" 1530 mm	86.55 (15.14)	39,26 (0,20)

Corner Connector Set

CODE	DESCRIPTION	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
ECC1	Right and Left	0.70 (0.04)	0,32 (0,001)

Case Pack: 1 set

Architect Specs

Posts:	Proprietary non-corrosive composite material.
Post Connectors:	Glass Filled Polypropylene.
Traverses:	Proprietary non-corrosive composite material.
Vented/Solid Shelf Plates:	Reinforced polypropylene with Camguard® Antimicrobial.
Corner Connectors:	Glass Filled Polypropylene.
Adjustable Foot:	Glass Filled Nylon.
Seismic Foot:	Stainless steel post and wide foot plate, 3 holes for bolts. (Bolts not provided).
Divider Bars:	Glass Filled Nylon.
Wall Fastener:	Stainless Steel.
Dovetails:	Resin Nylon.
Wedges:	Resin Polypropylene.

Optional Accessories

Seismic Foot (Bolts not provided)	☐ CSEQ3	Color: Silver	Case pack: 4 each
Wall Fastener	☐ CSWF	Color: Silver	Case pack: 4 each
Identification Tag 6"	☐ CSID6	Color: White/Clear	Case pack: 12 each
Identification Tag 3"	☐ CSID3	Color: White/Clear	Case pack: 12 each

Standard Color

☐ Brushed Graphite (580)

Approvals



* Does not include Wall Fastener and Seismic Foot.

COMPONENT

CAMBRO
TRUSTED FOR GENERATIONS™

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003

D081511