



PRODUCT FEATURES

- Dual purpose used wet or dry
- Auto fill
- Wet elements
- Overhead halogen lights
- 65mm deep full size pans supplied
- Glass supplied separately *

UNIT DIMENSIONS & SPECIFICATIONS

BAIN MARIE 75⁰ factory set point

| Model | Cabinet | | | bench cut out hole size | Pans | water fill litres | Operating Current | Connection | Voltage |
|-------|-----------|----------|-----------|-------------------------|-----------------------------|-------------------|-------------------|------------------|---------|
| | Length mm | Depth mm | Height mm | | | | | | |
| LSBM3 | 1145 | 690 | 555 | 1125x670 | 3 x 1/1 65mm Gastro Pans | 57 | 15 Amp | 20 amp lead only | 240V |

* prior to installation see, installation guidelines, ventilation requirements and drainage options documents

* GLASS AND GANTRY OPTIONS

When ordering a LS unit select the gantry glass type you require from the [GLASS OPTIONS](#) page in this document.

ELECTRICAL POWER

Electrical power cord 3000mm
1 phase connection required.

Unit can be hard wired to isolation switch or fitted with suitable heavy duty plug such as PDL 56 series or Commando style plug.

WATER DRAINAGE

Screw on stop cock valve drain pipe
Ideally drain connected to waste.
Overflow flexible waste pipe 19mm dia. 1000 mm length from valve must be connected to waste.

GASTRO PANS

Units supplied with 1/1 pans at 65mm deep, max pan depth is 100mm

