



## PRODUCT FEATURES

- Dual purpose used wet or dry
- Auto fill
- Wet elements
- Overhead halogen lights
- 65mm deep full size pans supplied
- Glass supplied separately \*

## UNIT DIMENSIONS & SPECIFICATIONS

BAIN MARIE 75<sup>0</sup> factory set point

| Model | Cabinet   |          |           | bench cut out hole size | Pans                        | water fill litres | Operating Current | Connection       | Voltage     |
|-------|-----------|----------|-----------|-------------------------|-----------------------------|-------------------|-------------------|------------------|-------------|
|       | Length mm | Depth mm | Height mm |                         |                             |                   |                   |                  | 50/60 Hertz |
| LSBM4 | 1485      | 690      | 555       | 1465x670                | 4 x 1/1<br>65mm Gastro Pans | 75                | 20 Amp            | 30 amp lead only | 240V        |

\* prior to installation see, installation guidelines, ventilation requirements and drainage options documents

## \* GLASS AND GANTRY OPTIONS

When ordering a LS unit select the gantry glass type you require from the [GLASS OPTIONS](#) page in this document.

### ELECTRICAL POWER

Electrical power cord 3000mm  
1 phase connection required.

Unit can be hard wired to isolation switch or fitted with suitable heavy duty plug such as PDL 56 series or Commando style plug.

### WATER DRAINAGE

Screw on stop cock valve drain pipe  
Ideally drain connected to waste.  
Overflow flexible waste pipe 19mm dia.1000 mm length from valve must be connected to waste.

### GASTRO PANS

Units supplied with 1/1 pans at 65mm deep, max pan depth is 100mm

