

## Individual Heat Lamps

These units are effective for overhead heating in food preparation and serving areas. Designed specifically to be wired in pairs and in series, Roband heat lamps maintain prepared food at the correct serving temperature, while enhancing presentation at the same time.

### FEATURES

- Stainless steel construction
- Long life globes
- Series wiring further extends globe life
- Easily replaceable globes
- Aesthetic cover design

### SPECIFICATIONS

	MODEL	DESCRIPTION	POWER Watts*	ELEC CON. Amps	DIMENSIONS w x d x h (mm)
A	HL22 <sup>†</sup>	500 W lamp only	250	10	190 x 120 x 50
	HL24 <sup>†</sup>	1000 W lamp only	500	10	270 x 120 x 50
	HL26 <sup>†</sup>	1500 W lamp only	750	10	335 x 120 x 50
B	HL22C <sup>†</sup>	HL22 with cover	250	10	270 x 120 x 80
	HL24C <sup>†</sup>	HL24 with cover	500	10	270 x 120 x 80
	HL26C <sup>†</sup>	HL26 with cover	750	10	335 x 120 x 80
C	HLC190	Cover to suit HL22	N/A	N/A	270 x 120 x 55
	HLC260	Cover to suit HL24	N/A	N/A	270 x 120 x 55
	HLC330	Cover to suit HL26	N/A	N/A	335 x 120 x 55

<sup>†</sup>Must be installed in pairs and wired in series. \*Total power output of 1 pair wired in series.

HL26 pictured



A

HL26C pictured



B

HLC330 pictured



C

## Fluorescent Lighting Assemblies

Roband fluorescent lamp assembly profiles match the aluminium extrusion from which the quartz lamp assemblies are manufactured.

Specifically designed for use in refrigerated displays or where illumination is required without heat, these units have a diffused perspex cover over the light. They also feature a simple mounting system and come complete with an isolating switch and a 10 amp plug and cord.

HF900 pictured



### SPECIFICATIONS

MODEL	DESCRIPTION	POWER Watts	ELEC CON. Amps	LENGTH mm
HF900	1 fluorescent globe	18	10	900
HF1500	1 fluorescent globe	36	10	1500