



Speed, Performance, Value - The Right Balance

- 5 weighing units (kg, g, lb, oz, lb:oz)
- Full range tare
- Zero Tracking
- Simple user-friendly operation
- Large backlit LCD display
- Non-slip adjustable levelling feet
- Overload protection
- Colour coded, sealed keypad
- Large stainless steel pan
- Modern low profile design
- Precision load cell technology
- Splashproof to protect from accidental spills
- External calibration
- Rechargeable battery up to 150 hours operation
- Auto sleep / power down function to save battery life
- Low battery indication
- Mains Power Cord
- Weighing
- Parts counting
- Percentage weighing



Technical Specifications

Model	LBK 3	LBK 6	LBK 12	LBK 30
Maximum capacity	3000g	6000g	12kg	30kg
Readability	0.5g	1g	2g	5g
Repeatability (S.D.)	0.5g	1g	2g	5g
Linearity (\pm)	1g	2g	4g	10g
Pan size	250 x 180mm			

General Specifications

Typical stabilisation time	2 Sec
Units of measurement	Gram (g), Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Operating temperature	0° - 40°C
Power supply	Mains power cord / internal rechargeable battery
Calibration	Automatic External
Display	Green backlit LCD display with 6 digits
Housing	ABS plastic with stainless steel platform
Overall dimensions (wxdxh)	250 x 307 x 110mm
Net weight	1.8kg

Key Accessories

- In-use Cover
- In-Use Cover pack of 5
- In-Use Cover pack of 10



Adam Equipment - offices worldwide

www.adamequipment.com