

Vaccine Refrigerators

Features:

- Digital controller with digital temperature display
- Temperature data logger included
- Dynamic fan forced cooling system with automatic defrosting
- Double glazed glass door
- White External and Interior Finish
- Internal LED light
- Frequency/voltage: 50Hz/220-240 V


- Leveling adjustable feet
- QCPP approved
- Plastic coated steel shelves
- Battery backup controller
- Refrigerant: R600a
- Ambient temperatures from +16°C to +32°C





MV30



Temperature data logger included



Battery backup for controller in case of power outage



Quality Care Pharmacy Program
An initiative of The Pharmacy Guild of Australia

Gross/Net volume: 30/29 L

Exterior dimensions in mm: 445w x 485d x 535h

Number of shelves: 3

Max. noise level: 50 dB

Temperature range: +2°C to +8°C


Gross/net weight: 29/27 kg

Energy consumption in 24h: 0.8 kWh



MV60



Temperature data logger included



Battery backup for controller in case of power outage



Quality Care Pharmacy Program
An initiative of The Pharmacy Guild of Australia

Gross/Net volume: 62/59 L

Exterior dimensions in mm: 445w x 485d x 725h

Number of shelves: 4

Max. noise level: 50 dB

Temperature range: +2°C to +8°C

Gross/net weight: 33/31 kg

Energy consumption in 24h: 0.8 kWh



MV150



Temperature data logger included



Battery backup for controller in case of power outage



Quality Care Pharmacy Program
An initiative of The Pharmacy Guild of Australia

Gross/Net volume: 148/145 L

Exterior dimensions in mm: 595w x 595d x 820h

Number of shelves: 4

Max. noise level: 50 dB

Temperature range: +2°C to +8°C

Gross/net weight: 45/42 kg

Energy consumption in 24h: 1.35 kWh