

Product Information

- Premium high-performance blast chiller
- R290 natural refrigerant for improved efficiency and lower environmental impact
- 7.0" touchscreen interface for simple operation
- Ozone sanitation connection for improved cabinet hygiene (Generator available in options)
- Soft and hard blast chilling, plus soft and hard blast freezing for flexible product control
- Dedicated cycles for pre-cooling, fish sanitation, ice cream hardening, bottle cooling and pastry and air defrosting
- Special cycle library with built-in recipes to support consistent results
- Internal core probe for accurate temperature monitoring
- Adjustable fan speeds for improved product control
- Large 78mm tray spacing for improved airflow
- WIFI and HACCP connection for data collection
- Door opening hook allows the cavity to breathe when not in use
- Heated door perimeter to reduce condensation
- Rounded internal corners for easier cleaning and improved hygiene
- CFC free high density polyurethane insulation
- Cataphoresis treated evaporator for improved rust protection
- Magnetic front panel with large condenser filter for easy access and maintenance
- External condensate drip tray
- Reversible left-hand hinged door (ex factory, on request)
- **24-months parts and labour warranty**



Specifications

Model	NAT.10
W x D x H (mm)	750 x 864 x 1620
Weight	188kg
Packed Dimensions (mm)	790 x 905 x 1770
Packed Weight	203kg
Internal Dimensions (mm)	650 x 433 x 810
Net Capacity (Litres)	228 L
Capacity in Trays	10 x 1/1G/N (H40-65) Optional configuration: 20 x 1/1G/N (H20) 20 x EN60/40 (H20) 15 x 5 L Gelato Pan (5 x optional grid rack required)
Blast Chilling Capacity (+90°C > -2°C in 90 mins)	45kg
Blast Freezing Capacity (+90°C > -18°C in 240 mins)	34kg
Refrigerant	R290 - 2 x 150 grams
Climate Class	5
Total Connected Load	2.7kW / 7.0A
Electrical Connection	3Ø+N+E 415VAC / 50Hz Onsite Connection

Legend

A Electrical Connection

Accessories

SPNOR.OZONEG	Plug in Ozone Generator
SPNOR.CAST02	Mobile castor kit -total height with castor kit 1648mm
SPNOR.PROBE4	Predisposition for 4 probes (includes one probe)-ex factory
SPNOR.PROBE	Additional probes only for predisposition units
CMGE.0927	1/1 GN S/S Grid Rack

