



SINGLE PAN ELECTRIC PASTA COOKER 450mm

PC8140E, PC8140E7



Overall Construction

- Pan 1.5mm 316 stainless steel with 10 year limited warranty
- Bull nose welded 1.5mm stainless steel
- Splashback 1.5mm stainless steel
- Side panels 1.2mm stainless steel
- Double skin door with 0.9mm stainless exterior
- 25mm (1") skimming overflow and pan drains drain valve
- 150mm legs in 63mm dia. heavy-duty 1.2mm stainless steel legs with adjustable feet
- 4 stainless steel baskets with moulded handle grips supplied standard
- Stainless steel wire basket support grid in pan

- High performance single pan pasta cooker
 PC8140E 10.5kW 3 phase
 PC8140E7 7.0kW 1 phase
- Heavy-duty 3 coil Incoloy 825 element
- Easy clean 316 grade stainless steel open pan with 10 year limited warranty
- 40L water capacity
- Integrated water fill and starch skimming water faucet
- Four stainless steel pasta baskets supplied
- Hinged basket drain stand
- Safety cut-out thermostat for empty pan/water boil out
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular
- Low back model (PCL) available

Controls

- Large easy to use knob heat resistant reinforced
- 3 power settings (boil-simmer-standby)
- Mechanical thermostat
- Thermostat range 30°C 110°C
- Fail safe over-temperature safety cut-out
- Element tilt switch for heating cut-out
- Indicator lights for power & heating
- Fine adjustment water faucet for pan filling and water refreshing/starch skimming

Cleaning and Servicing

- Open stainless steel pan for easy clean
- Hinged basket drain stand
- Removable basket support grid
- 25mm (1") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit

Technical data sheet for

SINGLE PAN ELECTRIC PASTA COOKER 450mm



Specifications

Pan size

Water capacity 40L

Width 365mm

Length 405mm

Basket immersion depth 165mm

4 stainless steel perforated baskets with moulded plastic handles 165mm square x 180mm deep

Stainless steel wire basket support grid

1 x 10.5kW Incoloy 825 heating element

1 x 7.0kW Incoloy 825 heating element (PC8140E7)

Electrical Requirements

PC8140E

10.5kW, 400-415V, 50/60Hz, 3P+N+E

L1 14.6A

12146A

L3 14.6A

PC8140E7

7.0kW, 220-240V, 50/60Hz, 1P+N+E L1 29.2A

Electrical Connection

56mm from RH side, 541mm from rear and

Water Connection

Cold water connection 50mm from left hand side, 556mm from rear and 150mm from floor R1/2 (BSP) male

Drain Connection

Drain must be connected to system suitable for boiling water discharge

1" BSP Male connection 118mm from left hand side, 470mm from rear, and 170mm from floor

DIMENSIONS

Width 450mm

Depth 805mm

Height 915mm

Incl. splashback 1130mm

Incl. low back 970mm

NETT WEIGHT

78kg

PACKING DATA

0.54m3, 120kg

Width 870mm

Depth 495mm

Height 1255mm

OPTIONS AT EXTRA COST


Rectangular baskets 320mm x 165mm Side splash guards

Joining caps

Plinth mounting

PC8140E





MOFFAT

Australia www.moffat.com.au New Zealand www.moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9202 6820 bgarcia@moffat.com.au

New Zealand Moffat Limited

Christchurch Telephone 03-389 1007 sales@moffat.co.nz

Auckland Telephone 09-574 3150 sales@moffat.co.nz





signed and manufactured by

MOFFET:

ISO99001 All Waldorf products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

Printed in New Zealand © Copyright Moffat Limited Moffat/BH/6864



