




Product Information

- Premium high-performance multi-function blast chiller with low-temperature cooking up to 85°C and controlled humidity
- R290 natural refrigerant for improved efficiency and lower environmental impact
- 7.0" touchscreen interface for simple operation
- Integrated ozone sanitation for improved cabinet hygiene
- Soft and hard blast chilling, plus soft and hard blast freezing for flexible product control
- Dedicated cycles for pre-cooling, fish sanitation, ice cream hardening, bottle cooling and pastry and air defrosting
- Special cycle library with built-in recipes to support consistent results
- Internal multi-point core probe for accurate temperature monitoring
- Adjustable fan speeds for improved product control
- Large 78mm tray spacing for improved airflow
- WIFI and HACCP connection for data collection
- Door opening hook allows the cavity to breathe when not in use
- Heated door perimeter to reduce condensation
- Rounded internal corners for easier cleaning and improved hygiene
- CFC free high density polyurethane insulation
- Cataphoresis treated evaporator for improved rust protection
- Magnetic front panel with large condenser filter for easy access and maintenance
- External condensate drip tray
- Reversible left-hand hinged door (ex factory, on request)
- 24-months parts and labour warranty**



Specifications

Standard Filter	PLUS.5.SF
Reverse Osmosis	PLUS.5.RO
W x D x H (mm)	750 x 864 x 970
Weight	124kg
Packed Dimensions (mm)	790 x 905 x 1120
Packed Weight	139kg
Internal Dimensions (mm)	650 x 433 x 410
Net Capacity (Litres)	115 L
Capacity in Trays	5 x 1/1G/N (H40-65) Optional configuration: 10 x 1/1G/N (H20) 10 x EN60/40 (H20) 6 x 5 L Gelato Pan (2 x optional grid rack required)
Blast Chilling Capacity (+90°C > 3°C in 90 mins)	23kg
Blast Freezing Capacity (+90°C > -18°C in 240 mins)	18kg
Refrigerant	R290 - 150 grams
Climate Class	5
Total Connected Load	1.6kW / 7.6A
Electrical Connection	240VAC / 50Hz 10A plug & lead



Legend

- A** Electrical Connection
- B** Water Inlet Connection

Accessories

SPNOR.CAST02	Mobile castor kit -total height with castor kit 998mm
SPNOR.PROBE4	Predisposition for 4 probes (includes one probe)-ex factory
SPNOR.PROBE	Additional probes only for predisposition units
CMGE.0927	1/1 GN S/S Grid Rack