

# SPD505AU10

Family	Dishwasher
Subfamily	Undercounter dishwashers
Type	Undercounter
Crockery	Crockery; Glasses; Cutlery; GN1/1 trays
Basket dimensions	500x500 mm
Control panel	Electronic
Rinse pump	HTR system
Wash pump	Standard
Power connection	230 V~ / 10 A / 2,1 kW / 50 Hz



## Distribution

Industries	Bar / Cafeterias / Bistros / Wine bars / Pubs; Hotels; Ristoranti / Catering; Bakeries / Pastry shops; Butcher shops / Delicatessens; Catering; Care facilities ; Commercial food services
------------	--

## Aesthetics

Serie	Ecoline	Led color	Red
-------	---------	-----------	-----

## Technical Features

Trays washing option	Yes	Max water hardness	12°f - 7°dH
Trays number	7 x GN 1/1 (530 x 325 mm)	Water inlet	Cold 15°C
Water consumption per cycle	3,2 l	Detergent load	Yes, manual
Wash temperature (min-max)	60 °C	Rinse load	Yes, manual
Rinse temperature (min-max)	85 °C	Usable load height	340 mm
		Depth with open door	1000 mm
		Product dimensions WxDxH	578x600x814 mm

Minimum water consumption per cycle	3,2 l
Water inlet	8°C
Max. inlet temperature	60°C

## Programs

Programs	3 automatic programs; Self-cleaning programs
Program options	Extra rinse; Clean water cycle
Program table	Electronic Ecoline dishwasher 500
Maximum basket/hour	40
Maximum dishes/hour	720
Maximum glasses/hour	1440

## Electrical Connection

Plug	(I) Australia	Wash pump power	700 W
Tank heating element power	1400 W	Default connection	7300 W
Boiler heating element power	1400 W		

## Interface

Display	4 digit	On/Off button	Yes
Number of buttons	5	Manual diagnostic	Yes

## Construction

Tank	Deep drawn	Filter	4-stages filter system
Construction	Partial double wall	Tank capacity	16 l
Tank material	Stainless steel AISI 304	Boiler capacity	6 l
Back panel	Galvanized	Boiler type	Artmosferic boiler
Upper washing system	One washing and one split rinse spray arms, stainless steel	Rumorosità	Lpa 54,5 dBA
Lower washing system	One washing and one combined rinse spray arms, stainless steel and plastic	Protection class	IPX4
Tank filter	Plastic	Adjustable feet	Yes
Door gasket	Only up	Drain max. height	600 mm
Rack guides	Embossed		

## Accessories Included


Dish basket	PB50D01	Water supply pipe	In acciaio Watermark
Cutlery basket	PHOOS02	Drain pipe	Yes - 2m
Flat basket	PB50G01		

## Equipments


Drain pump	Yes	Cycle counter	Yes
Peristaltic detergent dispenser	Yes, electronic control	Break tank	Yes
Peristaltic rinse-aid dispenser	Yes, electronic control	Partial renewal of water in the tank and built-in drain pump	Yes
Default chemicals dosing unit of measure	gr/lt	Water supply pipe diameter	16 mm
Rinse boiler Thermostop system	Yes - default	Drain supply pipe diameter	21,5 mm
Wash tank Thermostop system	Yes	Peristaltic detergent doser	Yes, manual
Wash pump soft start system	Yes	Peristaltic detergent doser	Yes, manual
Option for auto daily switch on	Yes, default OFF		

## Logistic Information


Width packed product	660 mm	Packed product dimensions	990X660X700
Depth packed product	700 mm	Net weight	53,000 kg
Height packed product	990 mm	Gross weight (kg)	61,000



## Compatible Accessories

**PB50D01**

Basket made of polypropylene for 18 plates  
500x500

**PB50T01**

Polypropylene basket for 8 trays GN  
1/1 h 40 mm

**PHOGR5**

Glass basket for 500x500 mm  
glasswashers

**PHOOS01**

Single basket in polypropylene for  
cutlery

**PHOOS02**

Basket in polypropylene for cutlery with  
6 compartments

**WH00S01**

Wire insert for 12 small dishes

**WS5**

Underframe for glasswashers 500mm

## Symbols glossary

---



...



...



5 stand filter



MAX.USABLE HEIGHT 340mm

---

## Benefit (TT)

---

### Interface

Control panel with electronic buttons

The electronic control panel features an intuitive interface with soft-touch buttons, allowing easy selection of one of the three wash programmes: short, medium, or intensive. There are also buttons for power, selection, and cycle start. The display provides real-time monitoring of the tank and boiler temperature, as well as diagnostics, ensuring effortless and immediate control of the main functions.

### 4-stage filtration system

Deep cleaning and spotless washes with the Patented 4-Stages Filtration System

The innovative Smeg filtration system consists of 4 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd stages, finer particles are captured at this filtration stage; the 3th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

### HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant temperature of 85°C. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

### Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

### Partial double skin

Optimised thermal and acoustic insulation

The double-skin design of the Ecoline features dual insulation on the door, top, and rear panel, while the side panels have a single layer of insulation. This structure optimises energy efficiency by minimising heat loss. Additionally, it provides effective acoustic insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

### Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

### **Soft-start system**

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.