

SPH505LAU15

Family	Dishwasher
Subfamily	Hoodtype dishwasher
Type	Hoodtype
Crockery	Crockery; Glasses; Cutlery; GN1/1 trays
Basket dimensions	500x500 mm
Control panel	Electronic
Rinse pump	HTR system
Wash pump	Standard
Power connection	230 V~ / 15 A / 3,4 kW / 50 Hz



Distribution

Solutions	Bars/Cafes; Schools
-----------	---------------------

Aesthetics

Serie	Ecoline	Led color	Green
-------	---------	-----------	-------

Technical Features

Trays washing option	Yes	Max water hardness	12°f - 7°dH
Trays number	7 x GN 1/1 (530 x 325 mm)	Water inlet	100-1000 kPa
Water consumption per cycle	3,2 l	Detergent load	Yes, manual
Wash temperature (min-max)	58 °C	Rinse load	Yes, manual
Rinse temperature (min-max)	87 °C	Usable load height	470 mm
Minimum water consumption per cycle	3,2 l	Maximum height with open hood	2138 mm
Water inlet	8°C	Product dimensions WxDxH	634x750x1523 mm
Max. inlet temperature	60°C		

Programs

Programs	3 automatic programs
Program options	Extra rinse; Clean water cycle
Program table	Electronic Ecoline hoodtype

Maximum basket/hour	40
Maximum dishes/hour	720
Maximum glasses/hour	1440

Electrical Connection

Plug	(I) Australia	Wash pump power	700 W
Tank heating element power	1400 W	Default connection	3400 W
Boiler heating element power	2600 W	Electrical connection option	230 V~ / 15 A / 3,4 kW / 50 Hz

Interface

Display	4 digit	Cycle progress alert	Yes
Number of buttons	5	End-cycle alert	Yes
On/Off button	Yes	Manual diagnostic	Yes

Construction

Tank Construction	Deep drawn Single-skin hood	Hood elevation system	Manual
Tank material	Stainless steel AISI 304	Filter	5-stages filter system
Back panel	Prepainted	Tank capacity	14 l
Upper washing system	One washing and one split rinse spray arms, stainless steel	Boiler capacity	10 l
Lower washing system	One washing and one split rinse spray arms, stainless steel	Rumorosità	Lpa 63,1 dBA
Tank filter	Stainless steel	Adjustable feet	Yes
		Drain max. height	1000 mm

Accessories Included

Dish basket	PB50D01	Water supply pipe	In acciaio Watermark
Cutlery basket	PHOOS02	Drain pipe	Yes - 2m
Flat basket	PB50G01		


Equipments

Drain pump	Yes	Option for auto daily switch on	Yes, default OFF
Peristaltic detergent dispenser	Yes, electronic control	Cycle counter	Yes
Peristaltic rinse-aid dispenser	Yes, electronic control	Break tank	Yes
Default chemicals dosing unit of measure	gr/lt	Partial renewal of water in the tank and built-in drain pump	Yes
Rinse boiler Thermostop system	Yes - default		

Wash tank Thermostop system	Yes	Water supply pipe diameter	16 mm
Wash pump soft start system	Yes	Drain supply pipe diameter	21,5 mm
Stand-by system	Yes	Peristaltic detergent doser	Yes, manual
		Peristaltic detergent doser	Yes, manual

Logistic Information

Width packed product	700 mm	Packed product dimensions	1700X700X900
Depth packed product	900 mm	Net weight	109,000 kg
Height packed product	1700 mm	Gross weight (kg)	128,000



Compatible Accessories



KITSONLIV

Probe level kit



PB50G01

Universal basket in polypropylene
500x500



PHOOS01

Single basket in polypropylene for
cutlery



PHOOS03

Basket in polypropylene with 6
compartment for cutlery for Capote



WB50G01

Universal wire basket with flat bottom
500x500



WB50G03

Wire basket for glasses with inclined
bottom 500x500



WB50T02

Wire basket for 5 trays 600x500




WT51200SHL

Entry table left side 1200mm




WT51200SL

Entry table left side 1200mm



PB50D01

Basket made of polypylene for 18
plates 500x500



PB50T01

Polypropylene basket for 8 trays GN
1/1 h 40 mm



PHOOS02

Basket in polypropylene for cutlery
with 6 compartments



WB50D01

Wire basket for 18 dishes and trays
500x500



WB50G02

Wire basket for glasses with inclined
bottom 500x500



WB50G04

Wire basket for glasses with inclined
bottom 500x500



WH00S01

Wire insert for 12 small dishes



WT51200SHR

Entry table right side 1200mm



WT51200SR

Entry table right side 1200mm



WT5700SL

Entry table left side 700mm



WT5700SR

Entry table right side 700mm



WTX51200

Exit table both sides 1200mm



WTX51200L

Exit table left side 1200mm



WTX51200R

Exit table right side 1200mm



WTX5700

Exit table both sides 700mm



WTX5700L

Exit table left side 700mm



WTX5700R

Exit table right side 700mm

Symbols glossary



...



...



5 STAGE FILTER



MAX. USABLE HEIGHT 470mm

Benefit (TT)

Interface

Control panel with electronic buttons

The electronic control panel features an intuitive interface with soft-touch buttons, allowing easy selection of one of the three wash programmes: short, medium, or intensive. There are also buttons for power, selection, and cycle start. The display provides real-time monitoring of the tank and boiler temperature, as well as diagnostics, ensuring effortless and immediate control of the main functions.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant temperature of 85°C. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Single-skin hood

Thermal and acoustic insulation guaranteed

The hood of the Ecoline features a single-skin structure designed to enhance energy efficiency by reducing heat dispersion. Additionally, it provides good sound insulation, helping to lower noise levels and ensure a quieter, more comfortable working environment for staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

Hood lift

Unprecedented comfort with the patented lifting system

The new ergonomic handle, combined with the patented lifting system, minimises the effort required to open and close the hood, limiting it to just 2.5 kg. This system ensures an exceptionally smooth and lightweight operation, helping to protect the operator's health and well-being, even during extended use.