


TCE1000

2 door upright glass door fridge

Our entry level General Display fridge, with EZICORE - a convenient & easy to remove refrigeration cartridge.

Quick Guide











Convenience Restaurants **Stores**



Hospitality Venues









Clubs / Pubs / Accommodation







Specifications TCE1000

	2 Glass Door
External	
Туре	Fridge
Dimensions (W x D x H mm)	1130 X 750 X 2200
Total floor area (m²)	0.85
Weight (kg)	205
Door (safety glass)	2
Door Design	Plastic frame, double glazed & argon filled
Controller	Electronic
Remote available	No
Breathes from / Expels air to	Upper front / top
Sign	Illuminated sign panel (LED)
Cabinet construction	Powder coated steel
Drainage (plumbing required)	No
Internal	
Gross volume (litres)	980
Lighting (vertical LED light)	2 (on the door)
No. of shelves (per door)	4
Shelf design	White plastic-coated wire
Total shelf area (m²)	1.84
Product facings (600ml PET bottle)	70
Total product loading	336 PETs
Performance	
MEPS category	M1 (food & drinks)
MEPS efficiency (kWh/24h/m²) @ Climate Class 3	6.96
Temperature range	o°C to 5°C
TEC (kWh/24h) @ Climate Class 3	7.5
High efficiency model	Yes
Maximum ambient temperature	35°C
Climate Class rating	4
Refrigeration system	Ezicore removable cartridge
Refrigerant / Charge	R134a / 260g
Total display area (m²)	80.1
<u> </u>	
Electrical power (kW)	0.720
Current draw (Amps)	3
10 Amp 3 pin plug	Yes
Controller & temp display	Electronic
Light switch	Seperate light switches for internal light & light box
	Seperate n ₆ ne smeares for internal n ₆ ne w n ₆ ne soo.