

GASTRONORM SLIDE BAR TROLLEYS delivered in flat pack



with vertical
secure bars

GN 1/1 bar slide trolleys

levels	L (mm)	w (mm)	H (mm)	d (mm)	A (mm)	B (mm)	weight (kg)	References		
								polyamid cover	vertical secure bars	stainless steel cover
15	656	457	1490	81	332	304	15	804 216	844 216	834 216
17	656	457	1650	81	332	304	16	804 217	844 217	834 217
20	656	457	1785	77	332	304	17	804 219	844 219	834 219

GN 2/1 bar slide trolleys

levels	L (mm)	w (mm)	H (mm)	d (mm)	A (mm)	B (mm)	weight (kg)	References		
								polyamid cover	vertical secure bars	stainless steel cover
15	773	659	1490	81	537	509	19	804 246	844 246	834 246
17	773	659	1650	81	537	509	21	804 247	844 247	834 247
20	773	659	1785	77	537	509	23	804 249	844 249	834 239

GENERALS CHARACTERISTICS

Made of food quality stainless steel with a chromium content more than 17,5%.

TUBE STRUCTURE:

- Uprights 25 x 25 mm section stainless steel tube, thickness 12/10 mm.
- 1 intermediate spacer on models with 17 and 20 levels and on GN 2/1 trolley with 15 levels

SLIDE BARS:

- Bright stainless steel sheet thickness 12/10 mm.
- Continuous argon welds with no added metal.
- L-shaped with runner stops at each end.

WHEELS:

- 4 swivel wheels Ø125 mm, of which 2 with brakes, non marking tyre.
- Annular wheel guards.
- Maximum load: 20 kg per level, maximum 200 kg. Top shelf of stainless steel plate thickness 12/10 mm on 6 level models, thickness 15/10 mm on 8 level models.
- Packed under plastic film.

END OF SERVICE LIFE:

- WEEE recycling channel - Syneg.
- Environmental specifications sheet available on request.

MADE TO REQUEST:

- Trolley with closing bar for transport in a vehicle.

