

## **VCS1 - SIDE ENGINE**

## Standard / Single Drawer

## **Product Information:**


- Modular refrigerated drawer system, providing bulk storage in a range of different configurations for extreme versatility (can be configured as a worktop or undercounter system)
- Energy efficient, insulated containers adopt 'hold the cold' technology when drawer is opened
- Low velocity cooling ensures stable temperatures and exceptional humidity control, prolonging shelf life by preventing food dehydration
- Precise temperature control in 1°C increments with adjustable digital temperature controller (15°C - -22°C)
- Designed to operate in ambient temperatures up to 40°C
- External drawer runners for hygiene and ease of cleaning
- · Low maintenance internal condenser
- Must be installed level with a 5mm fall to the rear
- 24 month parts and labour warranty, extended 5 year warranty available upon registration


**NOTE:** Adande units are not designed for use as a servery cabinet with multiple drawer openings and scooping of products such as: lce-cream/ Sorbet/ Gelato and or frozen berries.

Extended drawer openings will result in decreased efficiency of the refrigeration system and may lead to temperature uncertainty.

For optimal energy efficiency and temperature stability the drawers should always be closed firmly and as quickly as possible during use.







## Configurations:

Models	Base Configuration	Top Configuration	W x D x H (mm)	Weight	Max Loading Weight	Packed Dimensions (mm)	Packed Weight
VCS1.PT	Plinth Base	Cover Top	1100 x 700 x 420	91 kg	0 kg	1220 x 770 x 635	128 kg
VCS1.PW	Plinth Base	Solid Work Top	1100 x 700 x 429	99 kg	230 kg	1220 x 770 x 644	136 kg
VCS1.RW	Rollers	Solid Work Top	1100 x 700 x 458	100 kg	230 kg	1220 x 770 x 673	137 kg
VCS1.CT	Standard Castor	Cover Top	1100 x 700 x 493	93 kg	0 kg	1220 x 770 x 708	129 kg
VCS1.RHS	Rollers	Heatshield Top	1100 x 700 x 500	111 kg	230 kg	1220 x 770 x 715	147 kg
VCS1.CW	Standard Castor	Solid Work Top	1100 x 700 x 502	101 kg	300 kg	1220 x 770 x 717	137 kg
VCS1.CHS	Standard Castor	Heatshield Top	1100 x 700 x 543	111 kg	300 kg	1220 x 770 x 758	148 kg
VCS1.HCT	High Castor	Cover Top	1100 x 700 x 575	95 kg	0 kg	1220 x 770 x 790	131 kg
VCS1.HCW	High Castor	Solid Work Top	1100 x 700 x 584	103 kg	235 kg	1220 x 770 x 799	139 kg
VCS1.LHS	Adjustable Legs*	Heatshield Top	1100 x 700 x 597	111 kg	300kg	1220 x 770 x 812	147 kg
VCS1.HCHS	High Castor	Heatshield Top	1100 x 700 x 625	113 kg	235 kg	1220 x 770 x 840	150 kg
VCS1.LW	Adjustable Legs*	Solid Work Top	1100 x 700 x 557	100 kg	230	1220 x 770 x 640 *Adjustab	le Legs +/- 18mm 137 kg
VCS1.RT	Rollers	Cover Top	1100 x 700 x 450	92 kg	0 kg	1220 x 770 x 630	128 kg

Base Options:











Top Options:

— Cover Top (non load bearing)

Designed for undercounter

applications

Solid Work Top
Designed for load bearing applications

- Heatshield Top Protects unit tops exposed to temperatures up to 200°C

Revision: B - 14/11/2022 - 02

\*INSTALLATION NOTE: Hard-wired, gas and plumbed equipment cannot be directly installed onto the Adande unit. This equipment must be installed above the Adande unit using an independent equipment stand. Installation must be non-fixed to allow service access.

Due to continuous product research and development, the information contained herein is subject to change without notice.

www.stoddart.com.au www.stoddart.co.nz General Specifications:

Capacity 86 Litres 4 x 100mm deep 1/1 GN pans

6 x 65mm deep 1/1 GN pans

 Natural Refrigerant
 R600a

 Climate Class
 4

 Heat Rejection
 0.58 kW

 Db Rating
 50.6 - 54.2

Total Power 230VAC / 50Hz / 0.29kW 10A plug & lead

 Chiller
 Freezer

 Energy Usage kW/24hrs
 0.84 kW
 2.1 kW

 Running Current
 1.2A
 0.7A

